

# NISSAN CHEMICAL INDUSTRIES LTD.

Head Office:

No.2 Honmachi 1-chome Nihonbashi

Chuō-ku. Tokyo

Branch Office:

Dojima Bldg., 46 Kinugasa-cho

Kita-ku. Osaka

Factory:

Hakodate, Komatsugawa, Oji, Kinegawa, Toyama, Fushiki,

Nagoya, Kizugawa, Owada,

Onoda, Kagami.

水和剖

Products:

Agricultural Chemicals

DDT Powder DDTWettable

DDT Emulsion

BHC Powder, BHC Wettable

2.4-D Nissan

Chemical Fertilizers

Industrial Chemicals

Amino-acid Sauce

BHC

水和剂

除草剂

A.C.P. 社

極東代理店

安・過燐酸后灰 千代田化成肥料 各種工業薬品・アミノ酸調味料 化学機器・カーパイト・耐酸陶器

### 化学工業株式會社

営業所

大阪市北區絹笠町四六 (堂ビル五階)

下関・富山・名古屋・札幌・福岡

凾館・王子・小松川・木下川・富山・伏木 名古屋・木津川・大和田・小野田・鏡



家庭用 11.5% 100g ダスター人

水和劑.

乳劑

薬

Cチクロリン

#### 三菱化成工業株式會社



東京都中央区銀座西六/六 福岡縣/(幡市藤田五段新聞

研究所 川崎市久本鴨居町

大阪営業所 大阪市東区備後町二/五六(第二野村ビル)



### 旭硝子株式會社淀川工場

ASAHI GARASU K. K. YODOGAWA PLANT

No. 15-9 Ebieshin-machi, Fukushima-ku O aka, Japan Tel (46) 655~659

······

DDT POWDER

10% (YODOXIN)

DDT SPRAY

5% (YODOXIN)

DDT EMULSION 20%

BHC POWDER 70.5%, 1.0%

CAUSTIC SODA, SYNTHETIC-HYDROCHLORIC ACID CAUSTIC POTASH, & OTHER CHEMICAL PRODUCTS



For Letermination of Organic Halogen Compounds such as BHC, DDT, etc.

Characteristics of Shimadzu Pola-rograph.

- (1) The main parts of our polarograph, i.e. galvanometer, standard cell and transformer etc., are all encased in a compact housing, so that the whole polarograph may require a little space.
- (2) The front panel and side panel are all made of thick black ebonite plate and the wiring is covered by vinyl chloride so that the insuration may be perfect. As a result of the above perfect insuration, you can work with the polarograph even in the dense moisture, such as of rainy days.
- (3) The experimental work with the apparatus require no dark room, excepting the handling of photo-recording paper, e. g. its



exchange and its developing.

- (4). The built-in galvanometer is very sensitive, so the results obtained are very accurate.
- (5). Turning the knob, you can easily adjust the indicating beam of galvanome er at any desired position on the scale, without moving the body of the apparatus
- (6) Aided by the function of plus voltage supplying arrangement, polarograms of good accuracy ranging from 4V. to +4V. are made obtainable through a simple manipulation.
- (7) The installation of the motor to drive the potentiometer-drum or photo-drum is carefully made so that it may not exert any bad influence upon the sensitivity of the galvanometer.
- (8) The potentiometer-drum can be ran reversely through changeover of gears, while the motor does not.
- (9) The wiring is so arranged as to connect conveniently such auxiliary equipments as "Reducible device for magnitude of residual cu. rent", "Interfering arrangement for diffusion current" and "Voltage 'supplying arrangement".

## SHIMADZU SEISAKUSHO LTD.

Head Office; Kawaramachi Nijo, Kyoto, Japan

貯穀害虫防除削



( Y-BHC 1% トリクリン, ベンゾール液)



朝日農薬株式會社

大阪市東区今橋三丁目十二番地