TITLE:

Emission of Particulate Matter 2.5 (PM2.5) from Sewage Sludge Incinerators in Japan

AUTHOR(S):

Shiota, Kenji; Takaoka, Masaki; Yamaguchi, Shuji; Oshita, Kazuyuki

CITATION:

Shiota, Kenji ...[et al]. Emission of Particulate Matter 2.5 (PM2.5) from Sewage Sludge Incinerators in Japan. *Drying Technology* 2015, 33(11): 1286-1294

ISSUE DATE:

2015-04-15

URL:

<http://hdl.handle.net/2433/201955>

RIGHT:

This is an Accepted Manuscript of an article published by Taylor & Francis in 'Drying Technology: An International Journal (2015)', available online: <http://www.tandfonline.com/10.1080/07373937.2015.1026977>; The full-text file will be made open to the public on 15 April 2016 in accordance with publisher's 'Terms and Conditions for Self-Archiving'; This is not the published version. Please cite only the published version.; この論文は出版社版ではありません。引用の際には出版社版をご確認ください。

Article Title: Emission of particulate matter 2.5 (PM2.5) from sewage sludge incinerators in Japan

Journal name: Drying Technology

Corresponding author: Kenji Shiota

Kyoto University, Department of Environmental Eng., Graduate School of Engineering,
Nishikyo-ku, Kyoto, 615-8540 Japan

E-mail: shiota.kenji.4x@kyoto-u.ac.jp, Tel: +81-75-383-7550, Fax: +81-75-383-3338

Co-authors: Masaki Takaoka^{1,2}, E-mail: takaoka.masaki.4w@kyoto-u.ac.jp

Shuji Yamaguchi², E-mail: yamaguchi@epsehost.env.kyoto-u.ac.jp

Kazuyuki Oshita^{1,2}, E-mail: oshita.kazuyuki.6e@kyoto-u.ac.jp

1 Kyoto University, Department of Global Ecology, Graduate School of Global Environmental Studies

2 Kyoto University, Department of Environmental Eng., Graduate School of Engineering,
Nishikyo-ku, Kyoto, 615-8540 Japan

ACKNOWLEDGEMENT

This study was supported by the research grants from Osaka Bay Regional Offshore Environmental Improvement Center and The Environment Research and Technology Development Fund (220002). We greatly appreciate Shimadzu Techno-Research, INC. and relevant local governments for help with sampling at SSIs.

ABSTRACT

Because fine particulate matter ≤ 2.5 μm in diameter (PM_{2.5}) causes health problems, PM_{2.5} emissions are of concern. However, little research on stationary sources has been conducted. To determine the concentration and filtration behaviour of PM_{2.5}, dust was collected from five fluid bed sewage sludge incinerators (SSIs) sorted by particle size using cascade impactors. The average PM_{2.5} concentration was 0.00014–4.8 mg/Nm³. The total estimated amount of PM_{2.5} emissions from the SSIs for all plants in Japan was 0.96–8.9 tons/year. Since the SSIs with dry Electrostatic Precipitators (EP) contributed 75–99% of the total emissions, replacing dry EPs with Bag Filters would significantly reduce the PM_{2.5} emissions from SSI.

KEYWORDS

PM_{2.5}, sewage sludge incinerator, bag filter, electrostatic precipitator, emission

INTRODUCTION

In recent years, fine particulate matter ≤ 2.5 μm in diameter (PM_{2.5}) has attracted increasing attention because of its health risk and the high PM_{2.5} concentrations in some rapidly industrialising areas.^[1,2] Epidemiological studies have demonstrated a relationship between mortality and long-term exposure to PM_{2.5} in ambient air.^[3,4] Many international organisations have assessed the health risks of exposure to PM, and the European Union, United States, and World Health Organisation (WHO) established quality standards for ambient air in 2005^[5] and 2006.^[6,7] In Japan, PM_{2.5} was added to the Japanese environmental standards in September 2009. These hold that the annual average PM_{2.5} concentration should be less than 15 $\mu\text{g}/\text{m}^3$ and the daily average less than 35 $\mu\text{g}/\text{m}^3$.

Recently, the multinational European EBoDE-project estimated that particulate matter (PM) was associated with the highest disease burden (6 000–10 000 DALYs per million people), followed in order by second-hand smoke, noise, and radon. Disability-adjusted life years (DALYs) are a summary measure of population health combining mortality and morbidity.^[8] The International Agency for Research on Cancer (IARC) also classified PM as carcinogenic to humans.^[9]

As primary particles, sources of PM_{2.5} include both anthropogenic sources such as combustion plants and vehicle emissions, and natural sources such as yellow sand, etc. It is also notable that secondary particles produced from gases affect atmospheric PM_{2.5} levels. However, few studies have determined PM_{2.5} levels from sources other than ambient air and most of the studies of PM_{2.5} sources have examined mobile sources, with few direct measurements of PM_{2.5} in flue gases.^[10–12] To prevent PM_{2.5} emissions, it is necessary to examine the present state of PM_{2.5} emissions from stationary sources. We have investigated some stationary sources of PM_{2.5} in recent years.^[13,14]

In Japan, sewage sludge represents one of the largest sources of industrial waste, with amounts produced increasing with the increase in the population using sewage treatment systems. The overall treatment system produces ~2.2 million tons of dry sewage sludge (Dried Sludge; DS) annually.^[15] Incineration techniques are widely used for disposal of sewage sludge, this reduces the volume of sludge and transforms waste into solid incineration ash, which facilitates easy waste handling. Due to the small land area available

in Japan, it is difficult to dispose of large quantities of sludge without intermediate treatment. Therefore, ~68% (1.5 million tons-DS) of sludge was incinerated in sewage sludge incinerators (SSIs) in 2008.^[15] Incineration emits toxic substances such as dioxin^[16] and mercury^[17] as well as large quantities of dust and PM2.5. However, no recent study has measured PM2.5 emissions from SSIs.

This study focused on the emission of PM2.5 from SSIs. We collected dust samples from five SSI plants according to particle size using an Andersen stack sampler to evaluate the concentration, removal ability, emission factor, and emission mass of PM2.5 from SSIs. This paper assumes that PM2.5 from SSI is the primary particle in the SSI flue gases.

MATERIALS AND METHODS

Sewage Sludge Incineration plants

Dust sampling was carried out at five continuous fluidized-bed-type SSI plants with different dust collectors. Two of the five plants had dry electrostatic precipitators (EP; plants EP1 and EP2), and the remaining three plants had both EP and wet EP (plant EP+WEP), bag filter (BF; plant BF), and ceramic filter (CF; plant CF), respectively. Generally, EP removes dust from flue gases using an electrostatic force. The removal efficiency for 10 μm particles is more than 99.5%. WEP is an EP that includes cleaning equipment that rinses gases with water, which results in removal efficiency better than that provided by EP alone. Fabric filters such as BF and CF remove dust from flue gases by filtration. This type of filter has much higher dust removal efficiency than EP has, particularly for fine particles. The temperature resistance of CF is better than that of BF due to the materials used in their manufacture.^[18] All of the incinerators had fluidised beds, a popular type of incinerator for sewage sludge in Japan.^[19] The fluidized beds are heated to an annual average temperature between 820 and 854°C, and sewage sludge burns continuously at a rate that depends on the incineration capacity of each plant. The sewage sludge in cake form is partially dewatered by a dewatering system such as a belt filter press (plant EP1, EP2, and EP+WEP), centrifuge (plant BF), screw press and indirect heating (plant CF). The sludge cakes contained 74.6 to 84% moisture when wet and 70.6 to 86.0% organic matter content when dried; the composition of the sludge tended to be similar to each other and in good agreement with previous reports.^[20-24] Among these plants, operational conditions are similar with respect to the incinerator, coagulant, combustion temperature, and organic content in sludge cake. Figure 1 and Table 1 show a summary of the plant flow and an outline of technical data, respectively, for each SSI plant.

FIG. 1. Plant flow and sampling points

TABLE 1 Technical data for five SSI plants^[25]

Sampling

Sampling was carried out at five SSI plants: plants EP1, EP2, EP+WEP, BF, and plant CF, which were sampled during on May 12-14, 2010, November 19-21, 2012, May 26-28, 2010, July 11-13, 2012, and November 17-19, 2010, respectively. In all plants, samples were collected from the dust collector and stack inlets to evaluate the proportion removed by the air pollution control devices (APCDs). Fig. 1 shows the sampling points. Dust samples in SSI flue gas were collected isokinetically in nine particle size fractions (from submicron to approximately 10 μm) using Andersen stack samplers (AS-500, Tokyo Dylec, Japan) inserted into the flue gas ducts of five SSI plants. The sampling methods were based on Japanese Industrial Standards (JIS) Z8808 and K0302.^[26,27] The representative particle size at each stage of the cascade impactor is defined as the aerodynamic particle size at which 50% separation is achieved and was obtained using the following equation:

$$D_{p50n} = -1.26 \times \lambda + \sqrt{1.58 \times \lambda^2 + \frac{1.08 \times \pi \times N \times \Psi_{50} \times D_{cn}^3 \times (172 + 0.4 \times \theta_s) \times 10^{-1}}{4 \times q_s}} \quad (1)$$

D_{p50n} : 50% separation particle size at the n^{th} stage (μm)

N : number of jet nozzles at the n^{th} stage

D_{cn} : bore of the jet nozzles at the n^{th} stage (mm)

Ψ_{50} : inertia parameter for 50% separation by particle size

θ_s : flue gas temperature ($^{\circ}\text{C}$)

q_s : suction flow rate at the suction nozzle (L/min)

λ : mean free path of a gas molecule (μm)

In this formula, the mean free path of a gas molecule (λ) was obtained using equation (2).

$$\lambda = 2.10 \times 10^{-5} \times (172 + 0.4 \times \theta_s) \times \sqrt{(273 + \theta_s)} \quad (2)$$

A period of at least 5 min was required for sample collection at the dust collector inlets and 44 h at the stack inlets. Two impingers (one without solution and the other with 5% H_2O_2) were placed behind the samplers to remove moisture and to absorb any gaseous substances in flue gas that had removed dust. Samplings was carried out under stable conditions. Table 1 and FIG. 2. summarize the sampling conditions and sampling design, respectively.

TABLE 2 Sampling conditions

FIG. 2. Design for sampling dust in flue gas

Analysis

The quartz filters used for sampling were heated at 250 $^{\circ}\text{C}$ for 2 h and cooled to room temperature before sampling to remove volatile substances. Before and after sampling, each filter was dried and weighed in a

clean room kept at 21.5°C (upper: 23°C , lower: 20°C) and 35% relative humidity (upper: 40%, lower: 30%), using microbalances (M5P-F, Sartorius, USA, or XP26, METTLER TOLEDO, USA) at a sensitivity of 1 µg. To determine the PM2.5 fraction exactly, the fraction up to a diameter of 2.5 µm was divided linearly according to the upper and lower diameters defining the fraction.

RESULTS AND DISCUSSION

Dust concentration

Figure 3a shows mass distribution versus aerodynamic diameter at the inlet of the stack. In particular, more than 90% of dust collected from the stacks of EP1 and EP2 consisted of particles under 3 µm. Although 55-90% of the stack dusts from WEP and CF also tended to consist of particles under 3 µm, some stack dust fractions from WEP and CF and most from BF were collected in only small amounts, and their weight was negligible. Figure 3b shows mass distribution versus aerodynamic diameter at the inlet of the dust collector. Of the dusts collected from the collectors of EP1, EP2, and WEP, 80-90% consisted of particles under 10 µm. In contrast, 40-70% of dusts collected from the dust collectors of BF and CF tended to consist of particles over 5 µm. Pretreatment of flue gases with a cyclone in some plants can account for this differences in size distribution at the dust collector.^[18]

FIG. 3. Mass distribution of dust. (a) at inlet of stack, (b) at inlet of dust collector. Dp: aerodynamic diameter.

The total dust and PM2.5 concentrations at the dust collector and stack inlets at each SSI plant are shown in Figure 4. The total dust and PM2.5 concentrations were $<0.32\text{--}5,000 \pm 670$ and $<0.14\text{--}4,800 \pm 730$ µg/Nm³ (mean ± mean deviation), respectively, in the flue gas in the stacks. Ehrlich et al. and Tirler et al. reported that the PM2.5 concentrations in German and Italian waste incineration plants were 752 and 32.9 µg/Nm³, respectively^[10,12]. Our results for plants WEP, BF, and CF were within the same or smaller range, while the results for plants EP1 and EP2 were considerably larger. More than 55% of total dust in the stack consisted of PM2.5. This result is similar to those reported by Ehrlich et al.^[10] and Bounanno et al.^[11] The PM2.5 concentration at the stack inlet of plant BF was less than the annual average Japanese environmental standard (15 µg/m³). Plant BF operated a state-of-the-art APCD, and the PM2.5 concentrations remained less than 0.14 µg/Nm³. In contrast, the PM2.5 and total dust levels at plants EP1 and EP2 were considerably higher than those at the other plants. Similar results were reported previously for municipal solid waste incinerators^[13,14]. The respective total dust and PM2.5 concentrations in the dust collector inlet were 1.5 ± 0.5 and 0.43 ± 0.13 g/Nm³ in plant EP1, 0.45 ± 0.8 and 0.32 ± 0.7 g/Nm³ in plant EP2, 4.4 ± 0.3 and 1.9 ± 0.1 g/Nm³ in plant EP+WEP, 5.6 ± 0.3 and 0.51 ± 0.09 g/Nm³ in plant BF, and 3.9 ± 1.0 and 0.86 ± 0.09 g/Nm³ in plant CF. The BF, WEP, and CF removed PM2.5 efficiently, but not the EP.

FIG. 4. Total dust and PM2.5 concentrations in the dust collector inlet

and the stack inlets at SSI plants ; error bar is mean deviation.

Removal of PM2.5 by APCD

The removal efficiency of PM2.5 and dust from the plants was investigated to determine the relationship of PM2.5 and the dust concentration in the stack inlet for different dust collectors, where the removal efficiency was calculated as follows:

$$\eta = \left(1 - \frac{C_{oN} Q_{oN}}{C_{iN} Q_{iN}}\right) \times 100 \quad (3)$$

η : removal efficiency (%)

C_{iN} : dust or PM2.5 concentrations at the dust collector inlet of each plant (g/Nm³)

C_{oN} : dust or PM2.5 concentrations at the stack inlet of each plant (g/Nm³)

Q_{iN} : flow rate of flue gas at the dust collector inlet of each plant (Nm³/h)

Q_{oN} : flow rate of flue gas at the stack inlet of each plant (Nm³/h)

The results are shown in Table 3. Plants EP+WEP, BF, and CF removed more than 99.99% of the PM2.5 and total dust, demonstrating that those dust collectors are effective for particle emission control. Most importantly, BF was the best dust collector in terms of both the dust concentration in the stack inlet and removal efficiency. The EP at plants EP1 and EP2 were the least efficient collectors. These findings are similar to the results of studies of municipal solid waste incinerators^[13,14], in which the PM2.5 removal efficiency of BF was higher than that of EP. The European Environment Agency (EEA) reported that the PM2.5 removal efficiency was 77–98% for industrial waste incineration, including hazardous waste and sewage sludge with some APCDs.^[28] In 1996, a U.S. Environmental Protection Agency (US EPA) report^[29] suggested that advances in incineration and APCD technology have improved removal efficiency. Replacing dry EP with BF would improve the PM2.5 removal in SSIs.

Table 3 Removal efficiency of total dust and PM2.5 by APCDs

Calculating the PM2.5 Emission Factor from SSIs

To evaluate PM2.5 emissions from SSIs in Japan, we calculated the emission factor for PM2.5 from our results although there were insufficient samples taken at each SSI plant. We surveyed the number and incineration capacity of SSIs with each type of dust collector, and calculated the PM2.5 emissions. These methods are described in detail below. Dust removal efficiency is generally known to be higher in WEP, BF, and CF than in EP.^[18] Temperature resistance differs between BF and CF. Because these dust collectors have different characteristics, we calculated the emission factor for each dust collector separately (EP, WEP, BF, and CF). The factor for EP was the average of those calculated for plants EP1 and EP2. In this study, the emission factor is defined as the weight of PM2.5 per ton of sewage sludge incineration capacity. The emission factor is defined by the following equation:

$$Ef = \frac{24 \times Q \times A}{10^6 \times B} \quad (4)$$

Ef: emission factor, weight of PM2.5 per ton of the incineration capacity (g/ton-sludge cake)

Q: flow rate of flue gas at the stack inlet in the plant (Nm³/hour)

A: concentration of PM2.5 at the stack inlet (μg/Nm³)

B: incineration capacity of the plant (ton-sludge cake/day)

The resulting emission factors are shown in Table 4. The PM2.5 emission factor for the SSI with EP was 8.7 g/ton-sludge cake, whereas those for wet EP, BF or CF were less than 0.26 g/ton-sludge cake and BF had the lowest value. The US EPA has set 0.18 kg/Mg-DS as the PM2.5 emission factor for a fluidised bed incinerator for SSI with a scrubber; this equals 180 g/ton-DS or approximately 36 g/ton-sludge cake based on an 80% water content.^[30] The EEA set 0.004 kg/Mg-waste (4 g/ton-waste) as the default PM2.5 emission factor for industrial waste incineration, including hazardous waste and sewage sludge.^[28] Although the units and materials burned in these other studies differed, the results were similar to the values set by the US EPA and EEA, and the values for WEP, BF, and CF were considerably smaller. Therefore, advances in technology could improve the removal efficiency.

Table 4 Emission factors of PM2.5

The results of the survey of the number and incineration capacity of SSI plants with each type of dust collector (EP, WEP, BF, and CF) are shown in Table 5. This was based on a survey of SSI plants, to which 85 plants responded. The total incineration capacity was 9,950 ton/day, which is 48% of the total number of plants and 39.3% of total plant capacity, for all of the SSI plants in Japan.^[31]

Table 5 Results of survey on SSI plants and calculated PM2.5 emission values

The PM2.5 emissions are defined by the following equation:

$$E = \sum_{i=1}^4 \frac{Ef \times C}{10^6} \times \frac{Xi}{100} \quad (5)$$

E: annual emissions of PM2.5 from SSIs (ton/year)

Ef: PM2.5 emission factor from the SSIs (g/ton-sludge cake)

C: amount of sewage sludge burnt in SSIs annually (ton-DS/year)

X_i : relative incineration capacity of SSI plants with each type of dust collector (%)

The emission results are shown in Table 6. These calculations are outlined in detail below. There were 92 plants with no available information on dust collector type. We assumed that all of these 92 plants were equipped with EP, WEP, BF, or CF, representing cases I, II, III, and IV, respectively (in Table 5). The amount of sewage sludge burnt annually in SSIs is 1.5 million tons-DS/year, or 68% of the 2.2 million tons-DS/year produced annually; these amounts are on a dry weight basis.^[15] It is possible that the PM_{2.5} emissions are underestimated. The total estimated emissions of PM_{2.5} from SSIs were 0.96–8.9 tons/year, of which more than 75% was from SSIs equipped with EP. Sugiyama et al. estimated that the total PM_{2.5} emissions in 2000 in Japan were 252 kton, of which 49% was from mobile emission sources.^[32] Kannari et al. estimated that anthropogenic PM_{2.5} emissions in 2000 in Japan equalled 147 Gg, of which 12% was due to waste incineration and field burning.^[33] The PM_{2.5} emissions from SSIs in our study was less than 0.0035% of the total estimated by Sugiyama et al. and less than 0.006% that of Kannari et al., so the contribution of SSIs to the total PM_{2.5} emissions is negligible. The emission results in our study could be underestimated because of the difference in units between E_f (g/ton-sludge cake) and C (ton-DS/year), the difference in the real amount of burnt sewage sludge, and incineration capacity. Because most of the PM_{2.5} emissions might originate from plants with EP, replacing dry EP with BF could significantly reduce the PM_{2.5} emissions from SSIs.

Table 6 Calculated PM_{2.5} emission values

CONCLUSIONS

This study measured the concentrations and removal efficiency of PM_{2.5} and total dust in flue gas from five SSI plants. The average PM_{2.5} concentration in the stack inlet of the plant with BF was lower than the Japanese environmental standard for ambient air (15 $\mu\text{g}/\text{m}^3$ annually). In the plants with WEP or CF, the PM_{2.5} concentrations in the stack inlet were also close to the environmental standard (35 $\mu\text{g}/\text{m}^3$ daily). The removal efficiencies of the plants with these dust collectors exceeded 99.99%. The emission of PM_{2.5} as primary particles from these plants was very low. By contrast, the plants with EP not only had the highest PM_{2.5} concentrations in the stack inlets but also the lowest PM_{2.5} removal. The PM_{2.5} emission factor for SSIs using EP was 8.7 g/ton-sludge cake, whereas that with wet EP, BF, or CF was less than 0.26 g/ton-sludge cake. The total estimated emission of PM_{2.5} from SSI in Japan was 0.96–8.9 ton/year, which was less than 0.0035% of the total PM_{2.5} emissions and 0.006% of the anthropogenic PM_{2.5} emissions estimated for Japan for 2000, although these emissions could underestimate. Since the SSIs with dry EP contributed 75–99% to the total emissions, replacing a dry EP with BF would significantly reduce the PM_{2.5} from SSIs.

The results suggest that PM_{2.5} emissions as primary particles from some SSI plants were very low. Future work should determine the contribution of secondary particles from gaseous substances such as SO₂, HCl, and NO in ambient air.

REFERENCES

1. Cao, C.; Jiang, W.; Wang, B.; Fang, J.; Lang, J.; Tian, G.; Jiang, J.; F. Zhu, T. F. Inhalable Microorganisms in Beijing's PM_{2.5} and PM₁₀ Pollutants during a Severe Smog Event. *Environmental Science and Technology* **2014**, 48 (3), 1499–1507.
2. Cheng Z.; Jiang J.; Fajardo O.; Wang S.; Hao J. Characteristics and health impacts of particulate matter pollution in China (2001–2011). *Atmospheric Environment* **2013**, 65 (0), 186–194
3. Dockery, D.W.; Pope, C.A.; Xu, X.; Spengler, J.D.; Ware, J.H.; Fay, M.E.; Ferris, B.G.; Speizer, F.E. An association between air pollution and mortality in six U.S. cities. *New England Journal of Medicine* **1993**, 329, 1753–1759.
4. Pope, C. A.; Thun, M. J.; Namboodiri, M. M.; Dockery, D. W.; Evans, J. S.; Speizer, F. E.; Heath, C. W. Particulate air pollution as a predictor of mortality in a prospective study of U.S. adults. *American Journal of Respiratory and Critical Care Medicine* **1995**, 151, 669–674.
5. European Standard. *Ambient air quality standard gravimetric measurement method for the determination of the PM_{2.5} mass fraction of suspended particulate matter*; EN14907; 2005.
6. United States Environmental Protection Agency. 40 CFR, Parts 53 and 58; 2006.
7. World Health Organization. *WHO air quality guidelines for particulate matter, ozone, nitrogen dioxide and sulphur dioxide*. Global update 2005, Summary of risk assessment, WHO Geneva, 2006.
8. Hänninen, O.; Knol, A. EBoDE-Report. Environmental Perspectives on Environmental Burden of Disease Estimates for Nine Stressors in Six European Countries. National Institute for Health and Welfare (THL), 2011.
9. International Agency for Research on Cancer. *Outdoor air pollution a leading environmental cause of cancer death*. http://www.iarc.fr/en/media-centre/iarcnews/pdf/pr221_E.pdf (accessed 29 July 2014)
10. Ehrlich, C.; Noll, G.; Kalkoff, W. D.; Baumbach, G.; Dreiseidler, A. PM₁₀, PM_{2.5} and PM_{1.0}—Emissions from industrial plants—Results from measurement programmes in Germany. *Atmospheric Environment* **2007**, 41, 6236–6254.
11. Buonanno, G.; Ficco, G.; Stabile, L. Size distribution and number concentration of particles at the stack of a municipal waste incinerator, *Waste management* **2009**, 29, 749–755
12. Tirler W.; Angelucci G.; Bedin K.; Voto G.; Donegà M.; Minach L. Active sampling and analysis of dioxins and polyaromatic hydrocarbons bound to fine particles in the vicinity of a municipal solid waste incinerator. *Organohalogen Compounds* **2007**, 69, 2268–2271.
13. Shiota, K.; Imai, G.; Takaoka, M.; Kimoto, S.; Matsui, Y.; Oshita, K.; Mizuno, T.; Morisawa, S. The effect of countermeasures for dioxin removal on the emission of fine particles from municipal solid waste incinerators. *Journal of Japan Society for Atmospheric Environment* **2011**, 46, 224–232. (in Japanese)
14. Takaoka, M.; Shiota, K.; Imai, G.; Oshita, K.; Emission of particulate matter 2.5 (PM_{2.5}) from

- 303 municipal solid waste incinerators. *In Proceedings of 7th i-CIPEC*, Seoul, Korea, 2012; 156–162.
- 304 15. Japan Swage Works Association. *Sewage Works in Japan 2008, Flow chart of the year-on-year*
305 *treatment and utilization amount of sewage sludge in Japan*; 2010. [http://www.jswa.jp/data-](http://www.jswa.jp/data-room/data.html)
306 [room/data.html](http://www.jswa.jp/data-room/data.html) (accessed 29 July 2014) (in Japanese)
- 307 16. Tazaki, M. Energy efficiency in sewage sludge incineration system, Kyoto University Doctoral
308 Dissertation 2011. <http://hdl.handle.net/2433/151996> (in Japanese)
- 309 17. Takaoka M.; Domoto S.; Oshita K.; Takeda N.; Morisawa S. Mercury emission from sewage sludge
310 incineration in Japan. *Journal of Material Cycles Waste Management* **2012**, 14, 113-119.
- 311 18. Vehlow, J. Air pollution control systems in WtE units: An overview. *Waste Management* **2014**. in press.
- 312 19. Chen, G.; Yue, P. L.; Mujumdar, S. Sludge Dewatering and Drying. *Drying Technology* **2002**, 20, 883-
313 916.
- 314 20. Oshita, K.; Takaoka, M.; Nakajima, Y.; Morisawa, S.; Kanda, H.; Makino, H.; Takeda, N. Sewage
315 Sludge Dewatering Process Using Liquefied Dimethyl Ether as Solid Fuel. *Drying Technology* **2011**, 29,
316 624-632.
- 317 21. Tazaki, M.; Tsuno, H.; Takaoka, M.; Shimizu, K. Modeling of Sludge Behavior in a Steam Dryer.
318 *Drying Technology* **2011**, 29, 1748-1757.
- 319 22. Peregrina, C.; Arlabosse, P.; Lecomte, D.; Rudolph, V. Heat and Mass Transfer During Fry-Drying of
320 Sewage Sludge. *Drying Technology* **2006**, 24(7), 797-818.
- 321 23. Ayol, A.; Durak, G. Fate and Effects of Fry-Drying Application on Municipal Dewatered Sludge.
322 *Drying Technology* **2013**, 31, 350-358.
- 323 24. Tuan, P-A.; Mika, S.; Pirjo, I. Sewage Sludge Electro-Dewatering Treatment—A Review. *Drying*
324 *Technology* **2012**, 30, 691-706.
- 325 25. Japan Sewage Works Association. *Sewage Works in Japan 2011, Sludge Dewatering and Sludge*
326 *Incineration in Japan*; 2013. (in Japanese)
- 327 26. Japan Industrial Standard. *Methods of measuring dust concentration in flue gas*; JIS Z8808; 1995. (in
328 Japanese)
- 329 27. Japan Industrial Standard. *Measuring Method for Particle-size Distribution of Dusts in Flue Gas*; JIS
330 K0302; 1989. (in Japanese)
- 331 28. European Environment Agency. *EMEP/EEA air pollutant emission inventory guidebook 2013*,
332 <http://www.eea.europa.eu/publications/emep-eea-guidebook-2013> , 2013(accessed 25 March 2014)
- 333 29. United States Environmental Protection Agency. AP42, Fifth Edition, Volume1, Compilation of Air
334 Pollutant Emission Factors Vol.1. Stationary, Point and Area Sources Report, 1996.
- 335 30. United States Environmental Protection Agency. AP42, Fifth Edition, Volume I, Chapter 2.2 Sewage
336 Sludge Incineration, <http://www.epa.gov/ttnchie1/ap42/ch02/index.html>, 1994. (accessed 29 July 2014)
- 337 31. Japan Sewage Works Association. *Japan Sewage Statistics in 2008*; 2010. (in Japanese)
- 338 32. Sugiyama, T.; Nansai, K.; Tohno, S.; Yamamoto, K. Compilation and application of a primary PM2.5
339 emissions inventory with high sectoral resolution in Japan. *Atmospheric Environment* **2009**, 43, 759–768.
- 340 33. Kannari, A.; Tonooka, Y.; Baba, T.; Murano, K. Development of multiple-species 1 km 1 km resolution
341 hourly basis emissions inventory for Japan. *Atmospheric Environment* **2007**, 41, 3428–3439.

342

343 Figure and Table captions
 344
 345 FIG. 1. Plant flow and sampling points
 346 FIG. 2. Design for sampling dust in flue gas
 347 FIG. 3. Mass distribution of dust. (a) at inlet of stack, (b) at inlet of dust collector. D_p : aerodynamic
 348 diameter.
 349 FIG. 4. Total dust and PM_{2.5} concentrations in the dust collector inlet and the stack inlets at SSI plants;
 350 error bar is mean deviation.
 351
 352 TABLE 1 Technical data for five SSI plants
 353 TABLE 2 Sampling conditions
 354 TABLE 3 Removal efficiency of total dust and PM_{2.5} by APCDs
 355 TABLE 4 Emission factors of PM_{2.5}
 356 TABLE 5 Result of survey on SSI plants and calculated PM_{2.5} emission values; case I-IV are assumed
 357 cases that there were 92 plants with no available information on dust collector type. In case I, II, III, and
 358 IV, all of the 92 plants are assumed to be equipped with EP, WEP, BF, or CF, respectively
 359 TABLE 6 Calculated PM_{2.5} emission values; case I-IV are assumed cases that there were 92 plants with
 360 no available information on dust collector type. In case I, II, III, and IV all of the 92 plants are assumed to
 361 be equipped with EP, WEP, BF, or CF, respectively
 362

363

364

365 FIG. 1. Plant flow and sampling points

366

367

FIG. 2. Design for sampling dust in flue gas

372

373

374 FIG. 3. Mass distribution of dust. (a) at inlet of stack, (b) at inlet of dust collector. D_p : aerodynamic
375 diameter.

376

377

378

379 FIG. 4. Total dust and PM2.5 concentrations in the dust collector inlet and the stack inlets at SSI
380 plants; error bar is mean deviation.

381

382

383

TABLE 1
Technical data for five SSI plants

Plant Parameters	EP1	EP2	EP+WEP	BF	CF
Sludge incineration capacity (ton-sludge cake/day)	72	65	130	200	150
Incinerator	Fluidized bed	Fluidized bed	Fluidized bed	Fluidized bed	Fluidized bed
Annual mean of combustion temperature (°C)	850	820	850	854	850
Coagulant	polymer	polymer	polymer	polymer	polymer
Sludge dewatering	Belt filter press	Belt filter press	Belt filter press	Centrifuge	Screw press
Annual amount of sludge cake incineration (ton/year)	14,300	14,700	54,200 ^(a)	147,000 ^(a)	55,800 ^(a)
Sludge cake					
Water content (% wet basis)	84	74.6	76.8	80.6	77.8
Organic content (% dry basis)	70.6	86	80.5	81.8	78
Ash (ton/year)	798	658	4100 ^(a)	8100 ^(a)	2680 ^(a)
Reagent consumption in flue gas treatment	Sodium hydroxide solution	Sodium hydroxide solution	Sodium hydroxide solution	Sodium hydroxide solution	Sodium hydroxide solution
	at wet scrubber	at wet scrubber	at wet scrubber	at wet scrubber	at wet scrubber

EP: Electrostatic Precipitator , WEP: Wet Electrostatic Precipitator , BF: Bag Filter, CF: Ceramic Filter

(a): Sum amount contained other lines in the plant

TABLE 2
Sampling conditions

Plant	EP1		EP2		EP+WEP		BF		CF	
Sampling date (year/month/day)	2010/4/12	2010/4/12-14	2012/11/19	2012/11/19-21	2010/5/26	2010/5/26-28	2012/7/11	2012/7/11-13	2010/11/17	2010/11/17-19
Parameters										
Sampling points	Inlet of EP	Inlet of stack	Inlet of EP	Inlet of stack	Inlet of EP	Inlet of stack	Inlet of BF	Inlet of stack	Inlet of CF	Inlet of stack
Flue gas flow rate (m/s)	16.5	2.8-3.1	14.3	4.8	20.3	18.1-19.5	22.5	22.3-23.6	18.9	15.3-16.7
(Nm ³ /hour)	3,130	4,320-4,870	4,620	12,400-12,700	9,640	18,500-20,000	17,300	34,600-37,100	12,800	24,700-26,500
Flue gas temperature (°C)	276	30-35	338	134	296	69-80	202	198-215	316	186-202
Relative humidity (%)	22	3.2-3.4	27.4	4.3	43.3	4.4-7.0	45.9	1.6-3.6	35.5	2.5
O ₂ (%)	10.8	12.3	10.2	15.8-16.1	6	10.5-15.1	6.7	15.3	9.2	15.1-15.8
CO ₂ (%)	9.1	7.9	9.1	3.9-4.1	14.3	5.5-10.0	11.2	3.9-4.1	9.1	3.5-5.1
N ₂ (%)	80.1	79.8	80.7	80.0-80.1	79.7	79.4-79.5	82.1	80.6-80.8	81.7	79.8-80.7
Diameter of suction (mm)	6	10	6	10	6	4	4	4	6	4
Suction flow rate (m/s)	10.4	11.6	9.2	13.4	8.9	11	5.4	10	6.1	13.5
Suction time	6 min	44 hrs	5 min	48 hrs	5 min	44 hrs	5 min	47 hrs	5 min	48 hrs
Suction gas volume (Nm ³)	1	0.0626	30.8	0.0367	38.9	0.0443	27	0.027	28.4	0.0305
	2	0.0626	30.6	0.0367	37.7	0.0443	29.6	0.027	28.5	0.0305
	3	0.0627	30.6	-	-	0.0443	29.9	-	-	0.0305

EP: Electrostatic Precipitator , WEP: Wet Electrostatic Precipitator , BF: Bag Filter, CF: Ceramic Filter

393
394

395
396
397

TABLE 3					
Removal efficiency of total dust and PM2.5 by APCDs					
Removal efficiency (%)					
Plant	EP1	EP2	EP+WEP	BF	CF
PM2.5	98.75	98.75	99.99<	99.99<	99.99
Total	99.63	99.91	99.99<	99.99<	99.99<

398
399

TABLE 4					
Emission factors of PM2.5					
Plant	EP1	EP2	EP+WEP	BF	CF
APCD	Cyclone, EP, WS		Cyclone, EP, WS, WEP	BF, WS	CF, WS
Emission factor of PM2.5 (g/ton-sludge cake)	8.7		0.26	< 5.9 E-7	0.17
APCD: Air Pollution Control Device, EP: Electrostatic Precipitator□					
WEP: Wet Electrostatic Precipitator , BF: Bag Filter, CF: Ceramic Filter					
WS: Wet Scrubber					

400
401
402

TABLE 5

Result of survey on SSI plants and calculated PM_{2.5} emission value; case I-IV are assumed cases because there were 92 plants with no available information on dust collector type. In case I, II, III, and IV all of the 92 plants are assumed to be equipped with EP, WEP, BF, or CF, respectively

Dust collector type	Number of plants	Sum of incineration capacity (ton-sludge cake/day)	Ratio of incineration capacity (%)				Use of emission factor (g/ton-sludge cake)
			Case I	Case II	Case III	Case IV	
Cyclone, EP	24	1750	67.6	6.9	6.9	6.9	8.7
Cyclone, EP, WEP	14	2200	8.7	69.4	8.7	8.7	0.26
BF	34	3500	13.8	13.8	74.5	13.8	< 5.9 E-7
CF	13	2500	9.9	9.9	9.9	70.6	0.17
No information	92	15383	all of EP	all of EP+WEP	all of BF	all of CF	-
Whole of Japan	177	25333	100	100	100	100	-

EP: Electrostatic Precipitator, WEP: Wet Electrostatic Precipitator, BF: Bag Filter, CF: Ceramic Filter

TABLE 6

Calculated PM_{2.5} emission values; case I-IV are assumed cases because there were 92 plants with no available information on dust collector type. In case I, II, III, and IV all of the 92 plants are assumed to be equipped with EP, WEP, BF, or CF, respectively

Dust collector type	Case I	Case II	Case III	Case IV	Emission of PM _{2.5} (ton/year)
Cyclone, EP	8.8	0.90	0.90	0.90	0.90 - 8.8
Cyclone, EP, WEP	0.034	0.27	0.034	0.034	0.034 - 0.27
BF	1.2 E-7	1.2 E-7	6.7 E-7	1.2 E-7	< 1.2 E-7 - 6.7 E-7
CF	0.025	0.025	0.025	0.18	0.025 - 0.18
Sum	8.9	1.19	0.96	1.11	0.96 - 8.9

EP: Electrostatic Precipitator , WEP: Wet Electrostatic Precipitator

BF: Bag Filter, CF: Ceramic Filter

418 The English in this document has been checked by at least two professional editors, both native
419 speakers of English. For a certificate, please see:

420

421 <http://www.textcheck.com/certificate/gDWW2X>

422

423

424