TITLE:

Permeability of Granite Including Macro-Fracture Naturally Filled with Fine-Grained Minerals

AUTHOR(S):

Nara, Yoshitaka; Kato, Masaji; Niri, Ryuhei; Kohno, Masanori; Sato, Toshinori; Fukuda, Daisuke; Sato, Tsutomu; Takahashi, Manabu

CITATION:

Nara, Yoshitaka ...[et al]. Permeability of Granite Including Macro-Fracture Naturally Filled with Fine-Grained Minerals. Pure and Applied Geophysics 2018, 175(3): 917-927

ISSUE DATE:

2018-03

URL:

<http://hdl.handle.net/2433/230347>

RIGHT:

This is a post-peer-review, pre-copyedit version of an article published in 'Pure and Applied Geophysics'. The final authenticated version is available online at: <http://dx.doi.org/10.1007/s00024-017-1704-x>; The full-text file will be made open to the public on 01 March 2019 in accordance with publisher's 'Terms and Conditions for Self-Archiving'; この論文は出版社版ではありません。引用の際には出版社版をご確認ご利用ください。; This is not the published version. Please cite only the published version.

Permeability of granite including macro-fracture naturally filled with fine-grained
minerals

Yoshitaka Nara¹, Masaji Kato², Ryuhei Niri³, Masanori Kohno⁴, Toshinori Sato⁵,
Daisuke Fukuda², Tsutomu Sato², Manabu Takahashi⁶

*1. Department of Civil and Earth Resources Engineering, Graduate School of
Engineering, Kyoto University, Kyoto Daigaku Katsura, Nishikyo-ku, Kyoto 615-8540,
Japan.*

*2. Faculty of Engineering, Hokkaido University, Kita 13 Nishi 8, Kita-ku, Sapporo,
Hokkaido 060-8628, Japan.*

*3. Department of Civil Engineering, Faculty of Engineering, Tottori University, 4-101
Koyama-Minami, Tottori 680-8552, Japan.*

*4. Department of Management of Social Systems and Civil Engineering, Graduate
School of Engineering, Tottori University, 4-101 Koyama-Minami, Tottori 680-8552,
Japan.*

*5. Japan Atomic Energy Agency, 432-2 Hokushin, Horonobe-cho, Hokkaido 098-3224,
Japan.*

*6. National Institute of Advanced Industrial Sciences and Technology, 1-1-1 Higashi,
Tsukuba, Ibaraki 305-8567, Japan.*

Abstract

Information on the permeability of rock is essential for various geoengineering projects, such as geological disposal of radioactive wastes, hydrocarbon extraction, and natural hazard risk mitigation. It is especially important to investigate how fractures and pores influence the physical and transport properties of rock. Infiltration of groundwater through the damage zone fills fractures in granite with fine-grained minerals. However, the permeability of rock possessing a fracture naturally filled with fine-grained mineral grains has yet to be investigated. In this study, the permeabilities of granite samples, including a macro-fracture filled with clay and a mineral vein, are investigated. The permeability of granite with a fine-grained mineral vein agrees well with that of the intact sample, whereas the permeability of granite possessing a macro-fracture filled with clay is lower than that of the macro-fractured sample. The decrease in the permeability is due to the filling of fine-grained minerals and clay in the macro-fracture. It is concluded that the permeability of granite increases due to the existence of the fractures, but decreases upon filling them with fine-grained minerals.

Keywords: Permeability, Granite, Fracture, Clay, Mineral vein

1. Introduction

It is essential to investigate the permeability of rock and the influence of the fractures on various engineering projects and natural hazard risk mitigation. For geological disposal of radioactive wastes, the intensity of radioactivity of radionuclides should be reduced by both engineered barriers (e.g., a bentonite buffer) and natural barriers (e.g., a rock mass.) If a radioactive waste repository is located in an area where the hydraulic gradient and the permeability are high, the retardation of migration of radionuclides by these barriers may not be sufficient. The existence of fractures can be undesirable for geological disposal of radioactive wastes, because the higher density and connectivity of fractures increase the permeability (Gueguen and Dienes, 1989). In addition, fractures in rocks play an important role in the fluid flow and distribution of the pore pressure. Consequently, fractures greatly influence volcanic eruptions. On the other hand, fractures are essential to boost the flow of hydrocarbons (natural gas and oil) in a rock mass for oil and natural gas extraction.

Fractures and pores are ubiquitous on all scales in crustal rocks. In the upper crust, fractures and pores remarkably influence the physical and transport properties of rocks. The existence of fractures and pores makes rock more compliant (Brace, 1965; Walsh, 1965; Hazzard et al., 2000; Abe, 2016; Griffiths et al., 2017), weaker (Nara and Kaneko, 2006; Fujii et al., 2007; Nasser et al., 2005, 2007; Nara, 2015), and more permeable if they are connected together in a percolating network (Gueguen and Dienes, 1989; Gueguen et al., 1997; Sausse et al., 2001; Benson et al., 2006a; Chaki et al., 2008; Nasser et al., 2009; Nara et al., 2011a).

It is well known that the aperture of the fracture significantly affects the permeability of rock (Norton and Knapp, 1977; Witherspoon et al., 1980; Walsh, 1981; David, 1993;

Unger and Mase, 1993; Amadei and Illangasekare, 1994; Oron and Berkowitz, 1998; Suzuki et al., 1998). Nara et al. (2011a) reported that the introduction of open macro-fractures and micro-fractures increase the permeability of basalt when the initial permeability is low. The permeability decreases as the confining pressure increases due to the closure of fractures in basalt (Vinciguerra et al., 2005; Fortin et al., 2011; Nara et al., 2011a) and granite (Pratt et al., 1977; Kranz et al., 1979; Darot et al., 1992; Morrow and Lockner, 1997; Benson et al., 2006b). Wang et al. (2016) reported that the permeability of fractured rock decreases if the macro-fracture is filled with fine-grained particles. In addition, they showed that the permeability depends on the grain size of the particles filling the macro-fracture; the permeability decreases as the grain size decreases.

The fractures in rock are often filled naturally with fine-grained mineral grains (i.e., clay). According to Ishibashi et al. (2016), fractures in granite are filled with clay due to the infiltration of groundwater through the damage zone. Clay may alter the permeability, decreasing the fracture aperture. However, the permeability of rock containing a macro-fracture naturally filled with fine-grained mineral grains has yet to be investigated.

In this study, we examine the permeability of crystalline rock including a macro-fracture, a mineral vein, and a macro-fracture filled with fine-grained mineral grains such as clay. Specifically, we investigate whether the permeability of the macro-fractured rock can be recovered by sealing and healing the macro-fracture upon filling with fine-grained minerals.

2. Rock sample

The rock sample is Toki granite, which was obtained in the Mizunami Underground Research Laboratory. This material has widely been used in previous research (e.g., Schubnel et al., 2003; Lanaro et al., 2009; Nara et al., 2011b, c; Sanada et al., 2013; Yamamoto et al., 2013; Yamasaki et al., 2013; Hashiba and Fukui, 2016). Specifically, we used the rock core samples obtained from a 200-m depth in the Mizunami Underground Research Laboratory in Mizunami-City, Japan (Iwatsuki et al., 2005; Nara et al., 2011b; Yuguchi et al., 2012; Koike et al., 2015). The cores often include natural macro-fractures. Such macro-fractures are commonly filled with clay and fine-grained minerals, which are solidified and become a mineral vein. Figure 1 shows photos of the rock core samples of Toki granite. Figures 1a, b, and c show the core samples containing macro-fractures, a mineral vein, and clay fillings naturally included in rock, respectively.

In this study, we prepared four types of samples: an intact specimen (TG-i), a macro-fractured specimen without filling (TG-f), a specimen including a mineral vein (TG-v), and a specimen with a macro-fracture naturally filled by clay (TG-c). From these samples, we prepared cylindrical specimens with 50-mm diameters and 25-mm lengths for the permeability tests (Figure 2). Figure 3 shows photomicrographs of TG-i (Fig. 3a), TG-v (Fig. 3b), and TG-c (Fig. 3c) taken from thin sections (0.03-mm thick) under crossed nicols. The mineral grains in the vein in TG-v in Fig. 3b are mainly solidified strongly fine-grained feldspars (plagioclase and potash feldspar) and mica. The clay included in TG-c (Fig. 3c) consists mainly of illite and a small amount of carbonate minerals.

3. Methodology

3.1 Experimental Method

Before the permeability tests, TG-i and TG-f were saturated with distilled water.

Since TG-c can be fractured along the clay layer due to the weakening of illite by water (Francisca et al., 2005; Nara et al., 2011d, 2012), this specimen was saturated with a 1-M sodium chloride solution. Previous research demonstrated that crack propagation in rock containing clay is depressed in 1-M sodium chloride solution (Nara et al., 2014).

Similarly, TG-v was saturated in a 1-M sodium chloride solution.

To evaluate the permeability, we used the transient pulse method for TG-i, TG-v, and TG-c because this method is useful for samples with a low permeability (Brace et al., 1968; Hsieh et al., 1981; Zhang et al., 2000a). A hydraulic head pulse (the pore pressure pulse) was applied on the upstream side of the specimen. Then the difference between the upstream and downstream pore pressure decreased with elapsed time. The permeability was determined from this temporal decrease of pore pressure difference in the specimen.

Brace et al. (1968) introduced the following equation to evaluate the permeability by the transient pulse method:

$$\frac{\Delta h(t)}{H} = \frac{h_u(t) - h_d(t)}{H} = \exp \left\{ -\frac{KA}{l} \left(\frac{1}{S_u} + \frac{1}{S_d} \right) t \right\} \quad (1)$$

where t is the time, $\Delta h(t)$ is the upstream and downstream difference of the hydraulic head, $h_u(t)$ is the hydraulic head at the upstream, $h_d(t)$ is the hydraulic head at the downstream, H is the difference of the hydraulic head at $t = 0$, K is the permeability, A is the cross-sectional area of the specimen, l is the length of the specimen, S_u is the

compressional storage of the upstream reservoir, and S_d is the compressional storage of the upstream reservoir. Following the methodology of Zhang et al. (2000b), both S_u and S_d were set to $8.0 \times 10^{-10} \text{ m}^2$.

Because the permeability could be high for TG-f due to the existence of a macro-fracture, the permeability measurement of TG-f was conducted by the constant flow method (formerly named as flow pump method) (Olsen, 1966; Morin and Olsen, 1987; Esaki et al., 1996). The permeability of a material is determined by Darcy's law using the pressure difference induced by the imposed steady state constant flow rate. For the constant flow method, the permeability is evaluated using the following equation (Olsen, 1966):

$$K = \frac{Ql}{A(h_u - h_d)} \quad (2)$$

where Q is the flow rate.

3.2 Experimental Apparatus

Figure 4 illustrates the permeability measurement system used in this study. This system can be used to conduct various methods of permeability test. Here we used the constant flow method and the transient pulse method. The permeability measurement system mainly consists of the pressure vessel, the confining fluid controller, the pore fluid controller, the data logger, and the temperature controllers.

This system was placed in a temperature-controlled room. It was possible to reduce the temperature change during the measurement rigorously. All the measurements were acquired at a constant temperature of $22 \pm 0.1 \text{ }^\circ\text{C}$.

The values of the pressure difference between the upstream and the downstream pore

pressures is obtained from the differential pressure transducers. The accuracy was 0.35 kPa. The pore pressure was around 1 MPa for all measurements. Pressure to the rock specimens was applied using a syringe pump. For the transient pulse method, the applied pore pressure pulse was around 40 kPa (4% of the pore pressure). For the constant flow method, the flow rates were 0.5 ml/s, 0.25 ml/s, 0.15 ml/s, 0.10 ml/s, and 0.05 ml/s under effective confining pressures at 1-3 MPa, 3-4 MPa, 4-5 MPa, 5-7 MPa, and 7-9 MPa, respectively. These values were selected to create an equal upstream and downstream pore pressure difference for all measurements, because it is important to control the pore pressure difference between upstream and downstream to ensure the constant flow rate in the specimens.

The confining pressure was applied using the double plunger pump. The maximum pressure of the pressure vessel was 10 MPa. Measurements were acquired under confining pressures between 2 to 10 MPa. Consequently, the effective pressures ranged from 1 to 9 MPa.

4. Results

It was necessary to apply a small pressure pulse on the upstream side of the specimen during the transient pulse measurements to induce laminar flow in the specimen (Brace et al., 1968). Figure 5 shows the temporal changes of the upstream and downstream hydraulic pressure difference for TG-i (Fig. 5a), TG-v (Fig. 5b), and TG-c (Fig. 5c) at a 2-MPa confining pressure. In all cases, the hydraulic pressure difference decreased exponentially. We evaluated the permeability by applying Eq. (1) to the data shown in Fig. 5.

For TG-f, we used the constant flow method. Figure 6 shows an example of the temporal change of the upstream and downstream hydraulic pressure difference in TG-f under a confining pressure of 2 MPa, in which the flow rate was 0.5 ml/s. The average value between 150 to 250 s (18.5 kPa) was used to evaluate the permeability.

Figure 7 and Table 1 show the relationship between the permeability and the effective pressure. The permeability of TG-f was much higher than that of other specimens, and decreased remarkably as the effective pressure (confining pressure) increased. The permeability of TG-f decreased by more than one order of magnitude when the effective pressure increased from 1 MPa to 9 MPa. The permeability of TG-v agreed well with that of TG-i at all effective pressures. In addition, the values of the permeability of TG-i and TG-v were independent of the effective pressure. The permeability of TG-c was much lower than that of TG-f, but slightly higher than those of TG-i and TG-v. Moreover, the permeability of TG-c decreased as the effective pressure increased. The permeability of TG-c decreased by around one order of magnitude when the effective pressure increased from 1 MPa to 9 MPa.

5. Discussion

5.1 Permeability of intact and macro-fractured granite

The permeability of macro-fractured granite (TG-f) is much higher than that of intact granite (TG-i) (Fig. 7 and Table 1). In the pressure range of this study, it is 3–4 orders of magnitude higher, demonstrating that the introduction of a macro-fracture in granite increases the permeability significantly.

The difference of the permeability between TG-f and TG-i decreases as the effective pressure increases. This may be due to the remarkable decrease in the permeability of TG-f with increasing pressure. Nara et al. (2011) suggested that the closure of a macro-fracture under hydrostatic pressure decreases the permeability of macro-fractured low-porosity rock (Seljadalur basalt) even when the applied pressure is low. The permeability decrease for TG-f is attributed to the closure of the macro-fracture under hydrostatic pressure.

In contrast, the permeability of TG-i remains almost constant over the entire pressure range. Nara et al. (2011) reported that the closure of micro-fractures can decrease the permeability of intact low-porosity rock (Seljadalur basalt) if a high hydrostatic pressure is applied on the rock. In particular, Nara et al. (2011) indicated that the closure of the micro-fracture predominantly affects the decrease in the permeability of Seljadalur basalt when the hydrostatic pressure exceeds 20 MPa, which is higher than the pressure in this study. Thus, the change in permeability for the intact granite is negligible in this study due to the low applied pressure.

226 5.2 Permeability of granite including a mineral vein and macro-fracture with clays

227

228 Because the permeability of TG-v agrees well with that of the intact specimen (TG-i),
229 the original macro-fracture in granite is almost completely filled with fine-grained
230 minerals. In addition, the change of the permeability for TG-v is small, which is the
231 same tendency with TG-i. It is considered that the applied pressure in this study has a
232 negligible influence on the closure of fractures in TG-v as well as TG-i.

233 The macro-fracture in TG-c is partly filled with clay because the permeability of TG-
234 c is higher than that of the intact specimen (TG-i). The permeability of TG-c decreases
235 as the effective pressure increases (Fig. 7). The closure of the macro-fracture under
236 hydrostatic pressure induces the decrease in the permeability of TG-c.

237 The permeability of TG-c is much lower than that of TG-f. This is attributed to clay
238 filling the macro-fracture. The decrease in the aperture occurs in the fracture in TG-c,
239 decreasing the permeability.

240 According to Nara et al. (2011a), if three macro-fractures with almost same size are
241 included in a low-porosity rock (Seljadalur basalt), the permeability is around one order
242 of magnitude higher than that of the same rock with one macro-fracture. The position of
243 the macro-fracture naturally filled with clay in TG-c is not the central part of the
244 specimen (Fig. 2d). If the area of the macro-fracture is located in the central part of the
245 specimen and the size of the macro-fracture doubles, the permeability may also
246 increase. Because the size difference in this case is smaller than that of Nara et al.
247 (2011), the increase of the permeability should be less than one order even if the macro-
248 fracture is located the central part in TG-c. Therefore, the location of the macro-fracture
249 in TG-c has a negligible influence on the permeability.

250

251

5.3 Evaluation of hydraulic aperture

253

254 In general, the permeability is a measure of the ability of a porous material to allow
255 fluids to pass through it. The permeability also indicates this ability for a material with
256 low-porosity. In contrast, a measure of the ability to transmit fluids by the hydraulic
257 aperture is appropriate for a fracture. In the case of the parallel-plate flow in direction- x ,
258 flow rate Q is related to the aperture via the following equation (e.g., Bear, 1988):

$$259 \quad Q = -\frac{a^3 D \rho g}{12 \mu} \frac{dh}{dx} \quad (3)$$

260 where D is the diameter of the specimen, μ is the viscosity of the fluid, ρ is the density
261 of the fluid, g is the gravitational acceleration, and dh/dx is the gradient of the hydraulic
262 head.

263 The relationship between the flow rate and the permeability is expressed as (e.g.,
264 Bear, 1988):

$$265 \quad Q = -KA \frac{dh}{dx} \quad (4)$$

266 where A is the cross-sectional area of the specimen and is equal to $\pi D^2/4$. Then the
267 following equation is obtained:

$$268 \quad \frac{a^3 \rho g D}{12 \mu} = KA \quad (5)$$

269 Consequently,

$$270 \quad a = \sqrt[3]{\frac{3 \pi \mu D K}{\rho g}} \quad (6)$$

271 Using this equation, the hydraulic aperture a can be evaluated.

The evaluated hydraulic apertures for all specimens are shown at elevated effective confining pressures (Fig. 8). TG-f has the largest hydraulic aperture. The hydraulic aperture decreases with increasing the pressure for TG-f and TG-c, whereas TG-i and TG-v have a negligible dependence on the hydraulic aperture. The hydraulic aperture of TG-c is around one order of magnitude greater than the intact specimen. It is considered that almost 90% of the aperture of the macro-fracture in TG-c is filled with fine-grained clay.

Generally the existence of fractures and their network are undesirable for the geological disposal of radioactive wastes. According to Heap et al (2014), stylolites in the Jurassic limestone at Bule (France) are not barriers to fluid flow. However, in the case of granite, the permeability decreases as the aperture decreases for fractures naturally closed by clay, suggesting that the existence of fractures in granitic rocks is not problematic when considering the long-term use of an underground granite rock mass.

6. Conclusions

The permeability of Toki granite, including a macro-fracture filled with clay or a mineral vein, is investigated and compared with the permeability of intact and macro-fractured granite samples. The permeability of the macro-fractured granite is much higher than that of intact sample, and decreases as the effective confining pressure increases. The permeability of the sample with a fine-grained mineral vein agrees well with that of the intact sample, whereas the permeability of granite with a macro-fracture filled with clay is less than that of the macro-fractured granite.

The permeability of fractured granite decreases by filling with clay. The evaluation of the hydraulic aperture suggests that the permeability decreases upon filling the macro-fracture with fine-grained minerals and clay. Additionally, the presence of fractures increases the permeability of granite, but filling the features with fine-grained minerals decreases the permeability, which can be helpful for the geological disposal of radioactive wastes.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

302 **Acknowledgement**

303

304 This work was supported in part by a grant from the Ministry of Economy, Trade and
305 Industry (METI).

References

- Abe, S., 2016. Comparison of discrete element simulations to theoretical predictions of the elastic moduli of damaged rocks. *Int. J. Rock Mech. Min. Sci.* 88, 265-272.
- Amadei, B., Illangasekare, T., 1994. A mathematical model for flow and solute transport in non-homogeneous rock fractures. *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* 31, 719-731.
- Bear, J. *Dynamics of fluids in porous media*. New York: Dover Publications; 1988.
- Benson, P.M., Meredith, P.G., Schubnel, A., 2006a. Role of void space geometry in permeability evolution in crustal rocks at elevated pressure. *J. Geophys. Res.* 111, B12203, doi: 10.1029/2006JB004309.
- Benson, P., Schubnel, A., Vinciguerra, S., Trovato, C., Meredith, P., Young, R. P., 2006b. Modeling the permeability evolution of microcracked rocks from elastic wave velocity inversion at elevated isotropic pressure. *J. Geophys. Res.* 111, B04202, doi: 10.1029/2005JB003710.
- Brace, W.F., 1965. Some new measurements of linear compressibility of rocks. *J. Geophys. Res.* 70, 391-398.
- Brace, W.F., Walsh, J.B., Frangos, W.T., 1968. Permeability of granite under high pressure. *J. Geophys. Res.* 73, 2225-2236.
- Chaki, S., Takarli, M., Agbodjan, W.P., 2008. Influence of thermal damage on physical properties of a granite rock: porosity, permeability and ultrasonic wave evolutions. *Constr. Build. Mater.* 22, 1456-1461.
- Darot, M., Gueguen Y., Baratin, M., 1992. Permeability of thermally cracked granite. *Geophys. Res. Lett.* 19, 869-872.
- David, C., 1993. Geometry of flow paths for fluid transport in rocks. *J. Geophys. Res.*

- 331 98, 12267-12278.
- 332 Esaki, T., Zhang, M., Takeshita, A., Mitani, Y., 1996. Rigorous theoretical analysis of a
- 333 flow pump permeability test. *Geotech. Test. J.* 19, 241–246.
- 334 Fortin, J., Stanchits, S., Vinciguerra, S., Guèguen, Y., 2011. Influence of thermal and
- 335 mechanical cracks on permeability and elastic wave velocities in a basalt from Mt.
- 336 Etna volcano subjected to elevated pressure. *Tectonophysics* 503, 60-74.
- 337 Francisca, F., Yun, T.S., Ruppel, C., Santamarina, J.C., 2005. Geophysical and
- 338 geotechnical properties of near-seafloor sediments in the northern Gulf of Mexico
- 339 gas hydrate province. *Earth Planet. Sci. Lett.* 237, 924-939.
- 340 Fujii, Y., Takemura, T., Takahashi, M., Lin, W., 2007. Surface features of uniaxial
- 341 tensile fractures and their relation to rock anisotropy in Inada granite. *Int. J. Rock*
- 342 *Mech. Min. Sci.* 44, 98-107.
- 343 Griffiths, L., Heap, M.J., Xu, T., Chen, C., Baud, P., 2017. The influence of pore
- 344 geometry and orientation on the strength and stiffness of porous rock. *J. Struct.*
- 345 *Geol.* 96, 149-160.
- 346 Gueguen, Y., Dienes, J., 1989. Transport properties of rocks from statistics and
- 347 percolation. *Math. Geol.* 21, 1-13.
- 348 Gueguen, Y., Chelidze, T., Le Ravalec, M., 1997. Microstructures, percolation
- 349 thresholds, and rock physical properties. *Tectonophysics* 279, 23-35.
- 350 Hashiba, K., Fukui, K., 2016. Time-dependent behaviors of granite: Loading-rate
- 351 dependence, creep, and relaxation. *Rock Mech. Rock Eng.* 49, 2569-2580.
- 352 Hazzard, J.F., Young, R.P., Maxwell, S.C., 2000. Micromechanical modelling of
- 353 cracking and failure in brittle rocks. *J. Geophys. Res.* 105, 16683-16697.
- 354 Heap, M.J., Baud, P., Reuschlé, T., Meredith, P.G., 2014. Stylolites in limestones:
- 355 Barriers to fluid flow?, *Geology* 42, 51-54.

- 356 Hsieh, P.A., Tracy, J.V., Bredehoeft, J.D., Silliman, S.E., 1981. A transient laboratory
- 357 method for determining the hydraulic properties of ‘tight’ rocks—I. theory. *Int. J.*
- 358 *Rock Mech. Min. Sci. & Geomech. Abstr.* 18, 245-252.
- 359 Ishibashi, M., Yoshida, H., Sasao, E., Yuguchi, T., 2016. Long term behavior of
- 360 hydrogeological structures associated with faulting: An example from the deep
- 361 crystalline rock in the Mizunami URL, Central Japan. *Eng. Geol.* 208, 114-127.
- 362 Iwatsuki, T., Furue, R., Mie, H., Ioka, S., Mizuno, T., 2005. Hydrochemical baseline
- 363 condition of groundwater at the Mizunami underground research laboratory (MIU).
- 364 *Appl. Geochem.* 20, 2283–2302.
- 365 Koike, K., Kubo, T., Liu, C., Masoud, A., Amano, K., Kurihara, A., Matsuoka, T.,
- 366 Lanyon, B., 2015. 3D geostatistical modelling of fracture system in a granitic
- 367 massif to characterize hydraulic properties and fracture distribution.
- 368 *Tectonophysics* 660, 1-16.
- 369 Kranz, R.L., Frankel, A.D., Engelder, T., Scholz, C.H., 1979. The permeability of whole
- 370 and jointed Barre granite. *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* 16, 225-
- 371 234.
- 372 Lanaro, F., Sato, T., Nakama, S., 2009. Depth variability of compressive strength test
- 373 results of Toki granite from Shobasama and Mizunami construction sites, Japan.
- 374 *Rock Mech. Rock Eng.* 42, 611-629.
- 375 Morin, R.H., Olsen, H.W., 1987. Theoretical analysis of the transient pressure response
- 376 from a constant flow rate hydraulic conductivity test. *Water Resour. Res.* 23, 1461-
- 377 1470.
- 378 Morrow, C.A., Lockner, D.A., 1997. Permeability and porosity of the Illinois UPH 3
- 379 drillhole granite and a comparison with other deep drillhole rocks. *J. Geophys.*
- 380 *Res.* 102, 3067-3075.

- 381 Nara, Y., 2015. Effect of anisotropy on the long-term strength of granite. *Rock Mech.*
- 382 *Rock Eng.* 48, 959-969.
- 383 Nara, Y., Kaneko, K., 2006. Sub-critical crack growth in anisotropic rock. *Int. J. Rock*
- 384 *Mech. Min. Sci.* 43, 437-453.
- 385 Nara, Y., Meredith, P.G., Yoneda, T., Kaneko, K., 2011a. Influence of macro-fractures and
- 386 micro-fractures on permeability and elastic wave velocities in basalt at elevated
- 387 pressure. *Tectonophysics* 503, 52-59.
- 388 Nara, Y., Cho, S.H., Yoshizaki, T., Kaneko, K., Sato, T., Nakama, S., Matsui, H., 2011b.
- 389 Estimation of three-dimensional stress distribution and elastic moduli in rock mass of
- 390 the Tono area, *International Journal of the Japanese Committee for Rock Mechanics* 7,
- 391 1-9.
- 392 Nara, Y., Kato, H., Yoneda, T., Kaneko, K., 2011c. Determination of three-dimensional
- 393 microcrack distribution and principal axes for granite using a polyhedral specimen, *Int.*
- 394 *J. Rock Mech. Min. Sci.* 48, 316-335.
- 395 Nara, Y., Morimoto, K., Yoneda, T., Hiroyoshi, N., Kaneko, K., 2011d. Effects of
- 396 humidity and temperature on subcritical crack growth in sandstone. *Int. J. Solids*
- 397 *Struct.* 48, 1130-1140.
- 398 Nara, Y., Morimoto, K., Hiroyoshi, N., Yoneda, T., Kaneko, K., Benson, P.M., 2012.
- 399 Influence of relative humidity on fracture toughness of rock: implications for
- 400 subcritical crack growth. *Int. J. Solids Struct.* 49, 2471-2481.
- 401 Nara, Y., Nakabayashi, R., Maruyama, M., Hiroyoshi, N., Yoneda, Y., Kaneko, K., 2014.
- 402 Influences of electrolyte concentration on subcritical crack growth in sandstone in
- 403 water. *Eng. Geol.* 179, 41-49
- 404 Nasser, M.H.B., Mohanty, B., Robin, P.-Y.F., 2005. Characterization of microstructures
- 405 and fracture toughness in five granitic rocks. *Int. J. Rock Mech. Min. Sci.* 42, 450-

- 1 406 460.
- 2
- 3
- 4 407 Nasser, M.H.B., Schubnel, A., Young, R.P., 2007. Coupled evolutions of fracture
- 5
- 6 408 toughness and elastic wave velocities at high crack density in thermally treated
- 7
- 8 409 Westerly granite. *Int. J. Rock Mech. Min. Sci.* 44, 601-616.
- 9
- 10
- 11 410 Nasser, M.B.H., Schubnel, A., Benson, P.M., Young, R.P., 2009. Common evolution of
- 12
- 13 411 mechanical and transport properties in thermally cracked Westerly granite at
- 14
- 15 412 elevated hydrostatic pressure. *Pure Appl. Geophys.* 166, 927-948.
- 16
- 17
- 18 413 Norton, D., Knapp, R., 1977. Transport phenomena in hydrothermal systems: the nature
- 19
- 20 414 of porosity. *Am. J. Sci.* 227, 913-936.
- 21
- 22
- 23 415 Olsen, H.W., 1966. Darcy's law in saturated kaolinite. *Water Resour. Res.* 2, 287-295
- 24
- 25 416 Oron, A.P., Berkowitz, B., 1998. Flow in rock fractures: the local cubic law assumption
- 26
- 27 417 reexamined. *Water Resour. Res.* 34, 2811-2825.
- 28
- 29
- 30 418 Pratt, H.R., Swolfs, H.S., Brace, W.F., Black, A.D., Handin, J.W., 1977. Elastic and
- 31
- 32 419 transport properties of an in situ jointed granite. *Int. J. Rock Mech. Min. Sci. &*
- 33
- 34 420 *Geomech. Abstr.* 14, 35-45.
- 35
- 36
- 37 421 Sanada, H., Hikima, R., Tanno, T., Matsui, H., Sato, T., 2013. Application of differential
- 38
- 39 422 strain curve analysis to the Toki granite for in situ stress determination at the
- 40
- 41 423 Mizunami underground research laboratory, Japan. *Int. J. Rock Mech. Min. Sci.*
- 42
- 43 424 59, 50-56.
- 44
- 45
- 46 425 Sausse, J., Jacquot, E., Fritz, B., Leroy, J., Lespinasse, M., 2001. Evolution of crack
- 47
- 48 426 permeability during fluid-rock interaction. Example of the Brèzouard granite
- 49
- 50 427 (Vosges, France). *Tectonophysics* 336, 199-214.
- 51
- 52
- 53 428 Schubnel, A., Nishizawa, O., Masuda, K., Lei, X.J., Xue, Z., Gueguen, Y., 2003.
- 54
- 55 429 Velocity measurements and crack density determination during wet triaxial
- 56
- 57 430 experiments on Oshima and Toki granites. *Pure Appl. Geophys.* 160, 869-887.
- 58
- 59
- 60
- 61
- 62
- 63
- 64
- 65

- 431 Suzuki, K., Oda, M., Yamazaki, M., Kuwahara, T., 1998. Permeability change in granite
- 432 with crack growth during immersion in hot water. *Int. J. Rock Mech. Min. Sci.* 35,
- 433 907-921.
- 434 Unger, A. J. A., Mase, C.W., 1993. Numerical study of the hydromechanical behavior of
- 435 two rough fracture surfaces in contact. *Water Resour. Res.* 29, 2101-2114.
- 436 Vinciguerra, S., Trovato, C., Meredith, P.G., Benson, P.M., 2005. Relating seismic
- 437 velocities, thermal cracking and permeability in Mt. Etna and Iceland basalts. *Int.*
- 438 *J. Rock Mech. Min. Sci.* 42, 900-910.
- 439 Walsh, J.B., 1965. The effect of cracks on the compressibility of rock. *J. Geophys. Res.*
- 440 70, 381-389.
- 441 Walsh, J.B., 1981. Effect of pore pressure and confining pressure on fracture
- 442 permeability. *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* 18, 429-435.
- 443 Wang, G., Mitchell, T.M., Meredith, P.G., Nara, Y., Wu, Z., 2016. Influence of gouge
- 444 thickness on permeability of macro-fractured basalt. *J. Geophys. Res.* 121, 8472-8487.
- 445 Witherspoon, P.A., Wang, J.S.Y., Iwai, K., Gale, J.E., 1980. Validity of cubic law for fluid
- 446 flow in a deformable rock failure. *Water Resour. Res.* 16, 1016-1024.
- 447 Yamamoto, K., Yoshida, H., Akagawa, F., Nishimoto, S., Metcalfe, R., 2013. Redox front
- 448 penetration in the fractured Toki granite, central Japan: An analogue for redox
- 449 reactions and redox buffering in fractured crystalline host rocks for repositories of
- 450 long-lived radioactive waste. *Appl. Geochem.* 35, 75-87.
- 451 Yamasaki, S., Zwingmann, H., Yamada, K., Tagami, T., Umeda, K., 2013. Constraining the
- 452 timing of brittle deformation and faulting in the Toki granite, central Japan. *Chem.*
- 453 *Geol.* 351, 168-174.
- 454 Yuguchi, T., Tagami, M., Tsuruta, T., Nishiyama, T., 2012. Three-dimensional fracture
- 455 distribution in relation to local cooling in a granitic body: An example from the Toki

1
2 456 granitic pluton, Central Japan. Eng. Geol. 149-150, 35-46.
3
4 457 Zhang, M., Takahashi, M., Morin, R.H., Esaki, T., 2000. Evaluation and application of the
5
6 458 transient-pulse technique for determining the hydraulic properties of low-permeability
7
8 459 rocks – Part 1: theoretical evaluation. Geotech. Test. J. 23, 83-90.
9
10
11 460 Zhang, M., Takahashi, M., Morin, R.H., Esaki, T., 2000. Evaluation and application of the
12
13 461 transient-pulse technique for determining the hydraulic properties of low-permeability
14
15 462 rocks – Part 2: experimental application. Geotech. Test. J. 23, 91-99.
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

Table

Table 1 Summary of the hydraulic conductivity for Toki granite at elevated pressures

	Effective confining pressure [MPa]	Hydraulic conductivity [m/s]
Intact specimen (TG-i)	1.07	$3.75 \times 10^{-12} \pm 1.79 \times 10^{-14}$
	1.98	$4.66 \times 10^{-12} \pm 6.89 \times 10^{-14}$
	3.05	$3.98 \times 10^{-12} \pm 6.90 \times 10^{-14}$
	4.04	$2.97 \times 10^{-12} \pm 1.64 \times 10^{-14}$
	5.04	$2.78 \times 10^{-12} \pm 2.38 \times 10^{-14}$
	5.96	$2.62 \times 10^{-12} \pm 2.72 \times 10^{-14}$
	7.00	$2.27 \times 10^{-12} \pm 4.72 \times 10^{-14}$
	8.02	$3.34 \times 10^{-12} \pm 3.27 \times 10^{-14}$
Macro-fractured specimen without filling (TG-f)	0.95	$5.56 \times 10^{-8} \pm 2.54 \times 10^{-9}$
	2.97	$1.71 \times 10^{-8} \pm 5.28 \times 10^{-10}$
	3.78	$1.03 \times 10^{-8} \pm 4.25 \times 10^{-10}$
	4.94	$7.09 \times 10^{-9} \pm 2.35 \times 10^{-10}$
	6.87	$2.87 \times 10^{-9} \pm 9.90 \times 10^{-10}$
	8.94	$3.62 \times 10^{-9} \pm 9.20 \times 10^{-10}$
Specimen with a mineral vein (TG-v)	1.22	$8.63 \times 10^{-12} \pm 1.56 \times 10^{-13}$
	1.97	$6.42 \times 10^{-12} \pm 7.34 \times 10^{-14}$
	2.83	$5.65 \times 10^{-12} \pm 1.06 \times 10^{-13}$
	3.84	$6.70 \times 10^{-12} \pm 3.65 \times 10^{-14}$
	4.84	$5.90 \times 10^{-12} \pm 9.86 \times 10^{-14}$
	6.69	$4.76 \times 10^{-12} \pm 6.52 \times 10^{-14}$
	8.89	$4.33 \times 10^{-12} \pm 4.48 \times 10^{-14}$
Specimen with a macro-fracture filled with clay (TG-c)	0.97	$7.59 \times 10^{-11} \pm 2.13 \times 10^{-12}$
	2.02	$4.43 \times 10^{-11} \pm 1.01 \times 10^{-12}$
	3.03	$3.21 \times 10^{-11} \pm 4.96 \times 10^{-13}$
	4.08	$1.98 \times 10^{-11} \pm 3.70 \times 10^{-13}$
	5.03	$1.67 \times 10^{-11} \pm 1.64 \times 10^{-13}$
	7.01	$1.25 \times 10^{-11} \pm 5.16 \times 10^{-14}$
	9.03	$1.06 \times 10^{-11} \pm 4.94 \times 10^{-14}$

Figure caption

Fig. 1 Photos of Toki granite. (a): Rock core sample (65-mm diameter) with a macro-fracture, (b): Rock core sample (50-mm diameter) with a mineral vein, (c): Rock core sample (65-mm diameter) with clay filling.

Fig. 2 Photos of (a) the intact specimen (TG-i), (b) macro-fractured specimen (TG-f), (c) specimen with a vein of fine-grained minerals (TG-v), and (d) specimen with a macro-fracture filled with clay (TG-c). Diameter and length of the specimens are 50 and 25 mm, respectively.

Fig. 3 Photomicrographs of (a) the intact specimen (TG-i), (b) specimen with a vein of fine-grained minerals (TG-v), and (c) specimen with a macro-fracture filled with clay (TG-c). Length and height of the photomicrographs are 1.95 and 1.25 mm, respectively.

Fig. 4 Schematic of the permeability measurement system.

Fig. 5 Temporal changes of the upstream and downstream hydraulic pressure difference for (a) the intact specimen (TG-i), (b) specimen with a vein of fine-grained minerals (TG-v), and (c) specimen with a macro-fracture filled with clay (TG-c) at a confining pressure of 2 MPa obtained by the transient pulse method. The accuracy of the upstream and downstream hydraulic pressure difference was 0.35 kPa.

Fig. 6 Temporal change of the upstream and downstream hydraulic pressure difference in the macro-fractured specimen (TG-f) at a confining pressure of 2 MPa obtained by the constant flow method. The accuracy of the upstream and downstream hydraulic pressure difference was 0.35 kPa.

Fig. 7 Relationships between permeability and effective confining pressure for an intact sample, a macro-fractured sample, a sample containing a mineral vein, and a

1
2 492 sample containing a macro-fracture filled with clays of Toki granite.
3
4 493 Fig. 8 Relationships between hydraulic aperture of equivalent fracture and effective
5
6 494 confining pressure for Toki granite.
7
8 495
9
10 496
11
12
13 497 The English in this document has been checked by native speakers of English, from an
14
15
16 498 English editing service company:
17
18 499 <https://www.zenis.co.jp/eng/index.html>
19
20 500
21
22 501
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65

Figure1b

[Click here to download Figure Figure_1b\(core_vein\).jpg](#)

Figure1c

[Click here to download Figure Figure_1c\(core_clay\).jpg](#)