

Permeability of granite including macro-fracture naturally filled with fine-grained minerals

Yoshitaka Nara<sup>1</sup>, Masaji Kato<sup>2</sup>, Ryuhei Niri<sup>3</sup>, Masanori Kohno<sup>4</sup>, Toshinori Sato<sup>5</sup>,  
Daisuke Fukuda<sup>2</sup>, Tsutomu Sato<sup>2</sup>, Manabu Takahashi<sup>6</sup>

*1. Department of Civil and Earth Resources Engineering, Graduate School of Engineering, Kyoto University, Kyoto Daigaku Katsura, Nishikyo-ku, Kyoto 615-8540, Japan.*

*2. Faculty of Engineering, Hokkaido University, Kita 13 Nishi 8, Kita-ku, Sapporo, Hokkaido 060-8628, Japan.*

*3. Department of Civil Engineering, Faculty of Engineering, Tottori University, 4-101 Koyama-Minami, Tottori 680-8552, Japan.*

*4. Department of Management of Social Systems and Civil Engineering, Graduate School of Engineering, Tottori University, 4-101 Koyama-Minami, Tottori 680-8552, Japan.*

*5. Japan Atomic Energy Agency, 432-2 Hokushin, Horonobe-cho, Hokkaido 098-3224, Japan.*

*6. National Institute of Advanced Industrial Sciences and Technology, 1-1-1 Higashi, Tsukuba, Ibaraki 305-8567, Japan.*

## Abstract

Information on the permeability of rock is essential for various geoengineering projects, such as geological disposal of radioactive wastes, hydrocarbon extraction, and natural hazard risk mitigation. It is especially important to investigate how fractures and pores influence the physical and transport properties of rock. Infiltration of groundwater through the damage zone fills fractures in granite with fine-grained minerals. However, the permeability of rock possessing a fracture naturally filled with fine-grained mineral grains has yet to be investigated. In this study, the permeabilities of granite samples, including a macro-fracture filled with clay and a mineral vein, are investigated. The permeability of granite with a fine-grained mineral vein agrees well with that of the intact sample, whereas the permeability of granite possessing a macro-fracture filled with clay is lower than that of the macro-fractured sample. The decrease in the permeability is due to the filling of fine-grained minerals and clay in the macro-fracture. It is concluded that the permeability of granite increases due to the existence of the fractures, but decreases upon filling them with fine-grained minerals.

**Keywords:** Permeability, Granite, Fracture, Clay, Mineral vein

## 1. Introduction

It is essential to investigate the permeability of rock and the influence of the fractures on various engineering projects and natural hazard risk mitigation. For geological disposal of radioactive wastes, the intensity of radioactivity of radionuclides should be reduced by both engineered barriers (e.g., a bentonite buffer) and natural barriers (e.g., a rock mass.) If a radioactive waste repository is located in an area where the hydraulic gradient and the permeability are high, the retardation of migration of radionuclides by these barriers may not be sufficient. The existence of fractures can be undesirable for geological disposal of radioactive wastes, because the higher density and connectivity of fractures increase the permeability (Gueguen and Dienes, 1989). In addition, fractures in rocks play an important role in the fluid flow and distribution of the pore pressure. Consequently, fractures greatly influence volcanic eruptions. On the other hand, fractures are essential to boost the flow of hydrocarbons (natural gas and oil) in a rock mass for oil and natural gas extraction.

Fractures and pores are ubiquitous on all scales in crustal rocks. In the upper crust, fractures and pores remarkably influence the physical and transport properties of rocks. The existence of fractures and pores makes rock more compliant (Brace, 1965; Walsh, 1965; Hazzard et al., 2000; Abe, 2016; Griffiths et al., 2017), weaker (Nara and Kaneko, 2006; Fujii et al., 2007; Nasser et al., 2005, 2007; Nara, 2015), and more permeable if they are connected together in a percolating network (Gueguen and Dienes, 1989; Gueguen et al., 1997; Sausse et al., 2001; Benson et al., 2006a; Chaki et al., 2008; Nasser et al., 2009; Nara et al., 2011a).

It is well known that the aperture of the fracture significantly affects the permeability of rock (Norton and Knapp, 1977; Witherspoon et al., 1980; Walsh, 1981; David, 1993;

Unger and Mase, 1993; Amadei and Illangasekare, 1994; Oron and Berkowitz, 1998; Suzuki et al., 1998). Nara et al. (2011a) reported that the introduction of open macro-fractures and micro-fractures increase the permeability of basalt when the initial permeability is low. The permeability decreases as the confining pressure increases due to the closure of fractures in basalt (Vinciguerra et al., 2005; Fortin et al., 2011; Nara et al., 2011a) and granite (Pratt et al., 1977; Kranz et al., 1979; Darot et al., 1992; Morrow and Lockner, 1997; Benson et al., 2006b). Wang et al. (2016) reported that the permeability of fractured rock decreases if the macro-fracture is filled with fine-grained particles. In addition, they showed that the permeability depends on the grain size of the particles filling the macro-fracture; the permeability decreases as the grain size decreases.

The fractures in rock are often filled naturally with fine-grained mineral grains (i.e., clay). According to Ishibashi et al. (2016), fractures in granite are filled with clay due to the infiltration of groundwater through the damage zone. Clay may alter the permeability, decreasing the fracture aperture. However, the permeability of rock containing a macro-fracture naturally filled with fine-grained mineral grains has yet to be investigated.

In this study, we examine the permeability of crystalline rock including a macro-fracture, a mineral vein, and a macro-fracture filled with fine-grained mineral grains such as clay. Specifically, we investigate whether the permeability of the macro-fractured rock can be recovered by sealing and healing the macro-fracture upon filling with fine-grained minerals.

## 2. Rock sample

The rock sample is Toki granite, which was obtained in the Mizunami Underground Research Laboratory. This material has widely been used in previous research (e.g., Schubnel et al., 2003; Lanaro et al., 2009; Nara et al., 2011b, c; Sanada et al., 2013; Yamamoto et al., 2013; Yamasaki et al., 2013; Hashiba and Fukui, 2016). Specifically, we used the rock core samples obtained from a 200-m depth in the Mizunami Underground Research Laboratory in Mizunami-City, Japan (Iwatsuki et al., 2005; Nara et al., 2011b; Yuguchi et al., 2012; Koike et al., 2015). The cores often include natural macro-fractures. Such macro-fractures are commonly filled with clay and fine-grained minerals, which are solidified and become a mineral vein. Figure 1 shows photos of the rock core samples of Toki granite. Figures 1a, b, and c show the core samples containing macro-fractures, a mineral vein, and clay fillings naturally included in rock, respectively.

In this study, we prepared four types of samples: an intact specimen (TG-i), a macro-fractured specimen without filling (TG-f), a specimen including a mineral vein (TG-v), and a specimen with a macro-fracture naturally filled by clay (TG-c). From these samples, we prepared cylindrical specimens with 50-mm diameters and 25-mm lengths for the permeability tests (Figure 2). Figure 3 shows photomicrographs of TG-i (Fig. 3a), TG-v (Fig. 3b), and TG-c (Fig. 3c) taken from thin sections (0.03-mm thick) under crossed nicols. The mineral grains in the vein in TG-v in Fig. 3b are mainly solidified strongly fine-grained feldspars (plagioclase and potash feldspar) and mica. The clay included in TG-c (Fig. 3c) consists mainly of illite and a small amount of carbonate minerals.

### 3. Methodology

#### 3.1 Experimental Method

Before the permeability tests, TG-i and TG-f were saturated with distilled water.

Since TG-c can be fractured along the clay layer due to the weakening of illite by water (Francisca et al., 2005; Nara et al., 2011d, 2012), this specimen was saturated with a 1-M sodium chloride solution. Previous research demonstrated that crack propagation in rock containing clay is depressed in 1-M sodium chloride solution (Nara et al., 2014).

Similarly, TG-v was saturated in a 1-M sodium chloride solution.

To evaluate the permeability, we used the transient pulse method for TG-i, TG-v, and TG-c because this method is useful for samples with a low permeability (Brace et al., 1968; Hsieh et al., 1981; Zhang et al., 2000a). A hydraulic head pulse (the pore pressure pulse) was applied on the upstream side of the specimen. Then the difference between the upstream and downstream pore pressure decreased with elapsed time. The permeability was determined from this temporal decrease of pore pressure difference in the specimen.

Brace et al. (1968) introduced the following equation to evaluate the permeability by the transient pulse method:

$$\frac{\Delta h(t)}{H} = \frac{h_u(t) - h_d(t)}{H} = \exp\left\{-\frac{KA t}{l}\left(\frac{1}{S_u} + \frac{1}{S_d}\right)\right\} \quad (1)$$

where  $t$  is the time,  $\Delta h(t)$  is the upstream and downstream difference of the hydraulic head,  $h_u(t)$  is the hydraulic head at the upstream,  $h_d(t)$  is the hydraulic head at the downstream,  $H$  is the difference of the hydraulic head at  $t = 0$ ,  $K$  is the permeability,  $A$  is the cross-sectional area of the specimen,  $l$  is the length of the specimen,  $S_u$  is the

compressional storage of the upstream reservoir, and  $S_d$  is the compressional storage of the upstream reservoir. Following the methodology of Zhang et al. (2000b), both  $S_u$  and  $S_d$  were set to  $8.0 \times 10^{-10} \text{ m}^2$ .

Because the permeability could be high for TG-f due to the existence of a macro-fracture, the permeability measurement of TG-f was conducted by the constant flow method (formerly named as flow pump method) (Olsen, 1966; Morin and Olsen, 1987; Esaki et al., 1996). The permeability of a material is determined by Darcy's law using the pressure difference induced by the imposed steady state constant flow rate. For the constant flow method, the permeability is evaluated using the following equation (Olsen, 1966):

$$K = \frac{Ql}{A(h_u - h_d)} \quad (2)$$

where  $Q$  is the flow rate.

### 3.2 Experimental Apparatus

Figure 4 illustrates the permeability measurement system used in this study. This system can be used to conduct various methods of permeability test. Here we used the constant flow method and the transient pulse method. The permeability measurement system mainly consists of the pressure vessel, the confining fluid controller, the pore fluid controller, the data logger, and the temperature controllers.

This system was placed in a temperature-controlled room. It was possible to reduce the temperature change during the measurement rigorously. All the measurements were acquired at a constant temperature of  $22 \pm 0.1 \text{ }^\circ\text{C}$ .

The values of the pressure difference between the upstream and the downstream pore

pressures is obtained from the differential pressure transducers. The accuracy was 0.35 kPa. The pore pressure was around 1 MPa for all measurements. Pressure to the rock specimens was applied using a syringe pump. For the transient pulse method, the applied pore pressure pulse was around 40 kPa (4% of the pore pressure). For the constant flow method, the flow rates were 0.5 ml/s, 0.25 ml/s, 0.15 ml/s, 0.10 ml/s, and 0.05 ml/s under effective confining pressures at 1-3 MPa, 3-4 MPa, 4-5 MPa, 5-7 MPa, and 7-9 MPa, respectively. These values were selected to create an equal upstream and downstream pore pressure difference for all measurements, because it is important to control the pore pressure difference between upstream and downstream to ensure the constant flow rate in the specimens.

The confining pressure was applied using the double plunger pump. The maximum pressure of the pressure vessel was 10 MPa. Measurements were acquired under confining pressures between 2 to 10 MPa. Consequently, the effective pressures ranged from 1 to 9 MPa.

#### 4. Results

It was necessary to apply a small pressure pulse on the upstream side of the specimen during the transient pulse measurements to induce laminar flow in the specimen (Brace et al., 1968). Figure 5 shows the temporal changes of the upstream and downstream hydraulic pressure difference for TG-i (Fig. 5a), TG-v (Fig. 5b), and TG-c (Fig. 5c) at a 2-MPa confining pressure. In all cases, the hydraulic pressure difference decreased exponentially. We evaluated the permeability by applying Eq. (1) to the data shown in Fig. 5.

For TG-f, we used the constant flow method. Figure 6 shows an example of the temporal change of the upstream and downstream hydraulic pressure difference in TG-f under a confining pressure of 2 MPa, in which the flow rate was 0.5 ml/s. The average value between 150 to 250 s (18.5 kPa) was used to evaluate the permeability.

Figure 7 and Table 1 show the relationship between the permeability and the effective pressure. The permeability of TG-f was much higher than that of other specimens, and decreased remarkably as the effective pressure (confining pressure) increased. The permeability of TG-f decreased by more than one order of magnitude when the effective pressure increased from 1 MPa to 9 MPa. The permeability of TG-v agreed well with that of TG-i at all effective pressures. In addition, the values of the permeability of TG-i and TG-v were independent of the effective pressure. The permeability of TG-c was much lower than that of TG-f, but slightly higher than those of TG-i and TG-v. Moreover, the permeability of TG-c decreased as the effective pressure increased. The permeability of TG-c decreased by around one order of magnitude when the effective pressure increased from 1 MPa to 9 MPa.

## 5. Discussion

### 5.1 Permeability of intact and macro-fractured granite

The permeability of macro-fractured granite (TG-f) is much higher than that of intact granite (TG-i) (Fig. 7 and Table 1). In the pressure range of this study, it is 3–4 orders of magnitude higher, demonstrating that the introduction of a macro-fracture in granite increases the permeability significantly.

The difference of the permeability between TG-f and TG-i decreases as the effective pressure increases. This may be due to the remarkable decrease in the permeability of TG-f with increasing pressure. Nara et al. (2011) suggested that the closure of a macro-fracture under hydrostatic pressure decreases the permeability of macro-fractured low-porosity rock (Seljadalur basalt) even when the applied pressure is low. The permeability decrease for TG-f is attributed to the closure of the macro-fracture under hydrostatic pressure.

In contrast, the permeability of TG-i remains almost constant over the entire pressure range. Nara et al. (2011) reported that the closure of micro-fractures can decrease the permeability of intact low-porosity rock (Seljadalur basalt) if a high hydrostatic pressure is applied on the rock. In particular, Nara et al. (2011) indicated that the closure of the micro-fracture predominantly affects the decrease in the permeability of Seljadalur basalt when the hydrostatic pressure exceeds 20 MPa, which is higher than the pressure in this study. Thus, the change in permeability for the intact granite is negligible in this study due to the low applied pressure.

## 5.2 Permeability of granite including a mineral vein and macro-fracture with clays

Because the permeability of TG-v agrees well with that of the intact specimen (TG-i), the original macro-fracture in granite is almost completely filled with fine-grained minerals. In addition, the change of the permeability for TG-v is small, which is the same tendency with TG-i. It is considered that the applied pressure in this study has a negligible influence on the closure of fractures in TG-v as well as TG-i.

The macro-fracture in TG-c is partly filled with clay because the permeability of TG-c is higher than that of the intact specimen (TG-i). The permeability of TG-c decreases as the effective pressure increases (Fig. 7). The closure of the macro-fracture under hydrostatic pressure induces the decrease in the permeability of TG-c.

The permeability of TG-c is much lower than that of TG-f. This is attributed to clay filling the macro-fracture. The decrease in the aperture occurs in the fracture in TG-c, decreasing the permeability.

According to Nara et al. (2011a), if three macro-fractures with almost same size are included in a low-porosity rock (Seljadalur basalt), the permeability is around one order of magnitude higher than that of the same rock with one macro-fracture. The position of the macro-fracture naturally filled with clay in TG-c is not the central part of the specimen (Fig. 2d). If the area of the macro-fracture is located in the central part of the specimen and the size of the macro-fracture doubles, the permeability may also increase. Because the size difference in this case is smaller than that of Nara et al. (2011), the increase of the permeability should be less than one order even if the macro-fracture is located the central part in TG-c. Therefore, the location of the macro-fracture in TG-c has a negligible influence on the permeability.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

251

252 5.3 Evaluation of hydraulic aperture

253

254 In general, the permeability is a measure of the ability of a porous material to allow  
255 fluids to pass through it. The permeability also indicates this ability for a material with  
256 low-porosity. In contrast, a measure of the ability to transmit fluids by the hydraulic  
257 aperture is appropriate for a fracture. In the case of the parallel-plate flow in direction- $x$ ,  
258 flow rate  $Q$  is related to the aperture via the following equation (e.g., Bear, 1988):

259 
$$Q = -\frac{a^3 D \rho g}{12 \mu} \frac{dh}{dx} \quad (3)$$

260 where  $D$  is the diameter of the specimen,  $\mu$  is the viscosity of the fluid,  $\rho$  is the density  
261 of the fluid,  $g$  is the gravitational acceleration, and  $dh/dx$  is the gradient of the hydraulic  
262 head.

263 The relationship between the flow rate and the permeability is expressed as (e.g.,  
264 Bear, 1988):

265 
$$Q = -KA \frac{dh}{dx} \quad (4)$$

266 where  $A$  is the cross-sectional area of the specimen and is equal to  $\pi D^2/4$ . Then the  
267 following equation is obtained:

268 
$$\frac{a^3 \rho g D}{12 \mu} = KA \quad (5)$$

269 Consequently,

270 
$$a = \sqrt[3]{\frac{3 \pi \mu D K}{\rho g}} \quad (6)$$

271 Using this equation, the hydraulic aperture  $a$  can be evaluated.

1  
2 272 The evaluated hydraulic apertures for all specimens are shown at elevated effective  
3  
4 273 confining pressures (Fig. 8). TG-f has the largest hydraulic aperture. The hydraulic  
5  
6 274 aperture decreases with increasing the pressure for TG-f and TG-c, whereas TG-i and  
7  
8 275 TG-v have a negligible dependence on the hydraulic aperture. The hydraulic aperture of  
9  
10 276 TG-c is around one order of magnitude greater than the intact specimen. It is considered  
11  
12 277 that almost 90% of the aperture of the macro-fracture in TG-c is filled with fine-grained  
13  
14 278 clay.

15  
16  
17 279 Generally the existence of fractures and their network are undesirable for the  
18  
19 280 geological disposal of radioactive wastes. According to Heap et al (2014), stylolites in  
20  
21 281 the Jurassic limestone at Bule (France) are not barriers to fluid flow. However, in the  
22  
23 282 case of granite, the permeability decreases as the aperture decreases for fractures  
24  
25 283 naturally closed by clay, suggesting that the existence of fractures in granitic rocks is  
26  
27 284 not problematic when considering the long-term use of an underground granite rock  
28  
29 285 mass.  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

## 6. Conclusions

The permeability of Toki granite, including a macro-fracture filled with clay or a mineral vein, is investigated and compared with the permeability of intact and macro-fractured granite samples. The permeability of the macro-fractured granite is much higher than that of intact sample, and decreases as the effective confining pressure increases. The permeability of the sample with a fine-grained mineral vein agrees well with that of the intact sample, whereas the permeability of granite with a macro-fracture filled with clay is less than that of the macro-fractured granite.

The permeability of fractured granite decreases by filling with clay. The evaluation of the hydraulic aperture suggests that the permeability decreases upon filling the macro-fracture with fine-grained minerals and clay. Additionally, the presence of fractures increases the permeability of granite, but filling the features with fine-grained minerals decreases the permeability, which can be helpful for the geological disposal of radioactive wastes.

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

302     **Acknowledgement**

303

304     This work was supported in part by a grant from the Ministry of Economy, Trade and  
305     Industry (METI).

## References

- Abe, S., 2016. Comparison of discrete element simulations to theoretical predictions of the elastic moduli of damaged rocks. *Int. J. Rock Mech. Min. Sci.* 88, 265-272.
- Amadei, B., Illangasekare, T., 1994. A mathematical model for flow and solute transport in non-homogeneous rock fractures. *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* 31, 719-731.
- Bear, J. *Dynamics of fluids in porous media*. New York: Dover Publications; 1988.
- Benson, P.M., Meredith, P.G., Schubnel, A., 2006a. Role of void space geometry in permeability evolution in crustal rocks at elevated pressure. *J. Geophys. Res.* 111, B12203, doi: 10.1029/2006JB004309.
- Benson, P., Schubnel, A., Vinciguerra, S., Trovato, C., Meredith, P., Young, R. P., 2006b. Modeling the permeability evolution of microcracked rocks from elastic wave velocity inversion at elevated isotropic pressure. *J. Geophys. Res.* 111, B04202, doi: 10.1029/2005JB003710.
- Brace, W.F., 1965. Some new measurements of linear compressibility of rocks. *J. Geophys. Res.* 70, 391-398.
- Brace, W.F., Walsh, J.B., Frangos, W.T., 1968. Permeability of granite under high pressure. *J. Geophys. Res.* 73, 2225-2236.
- Chaki, S., Takarli, M., Agbodjan, W.P., 2008. Influence of thermal damage on physical properties of a granite rock: porosity, permeability and ultrasonic wave evolutions. *Constr. Build. Mater.* 22, 1456-1461.
- Darot, M., Gueguen Y., Baratin, M., 1992. Permeability of thermally cracked granite. *Geophys. Res. Lett.* 19, 869-872.
- David, C., 1993. Geometry of flow paths for fluid transport in rocks. *J. Geophys. Res.*

- 331 98, 12267-12278.
- 332 Esaki, T., Zhang, M., Takeshita, A., Mitani, Y., 1996. Rigorous theoretical analysis of a
- 333 flow pump permeability test. *Geotech. Test. J.* 19, 241–246.
- 334 Fortin, J., Stanchits, S., Vinciguerra, S., Guèguen, Y., 2011. Influence of thermal and
- 335 mechanical cracks on permeability and elastic wave velocities in a basalt from Mt.
- 336 Etna volcano subjected to elevated pressure. *Tectonophysics* 503, 60-74.
- 337 Francisca, F., Yun, T.S., Ruppel, C., Santamarina, J.C., 2005. Geophysical and
- 338 geotechnical properties of near-seafloor sediments in the northern Gulf of Mexico
- 339 gas hydrate province. *Earth Planet. Sci. Lett.* 237, 924-939.
- 340 Fujii, Y., Takemura, T., Takahashi, M., Lin, W., 2007. Surface features of uniaxial
- 341 tensile fractures and their relation to rock anisotropy in Inada granite. *Int. J. Rock*
- 342 *Mech. Min. Sci.* 44, 98-107.
- 343 Griffiths, L., Heap, M.J., Xu, T., Chen, C., Baud, P., 2017. The influence of pore
- 344 geometry and orientation on the strength and stiffness of porous rock. *J. Struct.*
- 345 *Geol.* 96, 149-160.
- 346 Gueguen, Y., Dienes, J., 1989. Transport properties of rocks from statistics and
- 347 percolation. *Math. Geol.* 21, 1-13.
- 348 Gueguen, Y., Chelidze, T., Le Ravalec, M., 1997. Microstructures, percolation
- 349 thresholds, and rock physical properties. *Tectonophysics* 279, 23-35.
- 350 Hashiba, K., Fukui, K., 2016. Time-dependent behaviors of granite: Loading-rate
- 351 dependence, creep, and relaxation. *Rock Mech. Rock Eng.* 49, 2569-2580.
- 352 Hazzard, J.F., Young, R.P., Maxwell, S.C., 2000. Micromechanical modelling of
- 353 cracking and failure in brittle rocks. *J. Geophys. Res.* 105, 16683-16697.
- 354 Heap, M.J., Baud, P., Reuschlé, T., Meredith, P.G., 2014. Stylolites in limestones:
- 355 Barriers to fluid flow?, *Geology* 42, 51-54.

Hsieh, P.A., Tracy, J.V., Bredehoeft, J.D., Silliman, S.E., 1981. A transient laboratory method for determining the hydraulic properties of 'tight' rocks—I. theory. *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* 18, 245-252.

Ishibashi, M., Yoshida, H., Sasao, E., Yuguchi, T., 2016. Long term behavior of hydrogeological structures associated with faulting: An example from the deep crystalline rock in the Mizunami URL, Central Japan. *Eng. Geol.* 208, 114-127.

Iwatsuki, T., Furue, R., Mie, H., Ioka, S., Mizuno, T., 2005. Hydrochemical baseline condition of groundwater at the Mizunami underground research laboratory (MIU). *Appl. Geochem.* 20, 2283–2302.

Koike, K., Kubo, T., Liu, C., Masoud, A., Amano, K., Kurihara, A., Matsuoka, T., Lanyon, B., 2015. 3D geostatistical modelling of fracture system in a granitic massif to characterize hydraulic properties and fracture distribution. *Tectonophysics* 660, 1-16.

Kranz, R.L., Frankel, A.D., Engelder, T., Scholz, C.H., 1979. The permeability of whole and jointed Barre granite. *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* 16, 225-234.

Lanaro, F., Sato, T., Nakama, S., 2009. Depth variability of compressive strength test results of Toki granite from Shobasama and Mizunami construction sites, Japan. *Rock Mech. Rock Eng.* 42, 611-629.

Morin, R.H., Olsen, H.W., 1987. Theoretical analysis of the transient pressure response from a constant flow rate hydraulic conductivity test. *Water Resour. Res.* 23, 1461-1470.

Morrow, C.A., Lockner, D.A., 1997. Permeability and porosity of the Illinois UPH 3 drillhole granite and a comparison with other deep drillhole rocks. *J. Geophys. Res.* 102, 3067-3075.

- 381 Nara, Y., 2015. Effect of anisotropy on the long-term strength of granite. *Rock Mech.*
- 382 *Rock Eng.* 48, 959-969.
- 383 Nara, Y., Kaneko, K., 2006. Sub-critical crack growth in anisotropic rock. *Int. J. Rock*
- 384 *Mech. Min. Sci.* 43, 437-453.
- 385 Nara, Y., Meredith, P.G., Yoneda, T., Kaneko, K., 2011a. Influence of macro-fractures and
- 386 micro-fractures on permeability and elastic wave velocities in basalt at elevated
- 387 pressure. *Tectonophysics* 503, 52-59.
- 388 Nara, Y., Cho, S.H., Yoshizaki, T., Kaneko, K., Sato, T., Nakama, S., Matsui, H., 2011b.
- 389 Estimation of three-dimensional stress distribution and elastic moduli in rock mass of
- 390 the Tono area, *International Journal of the Japanese Committee for Rock Mechanics* 7,
- 391 1-9.
- 392 Nara, Y., Kato, H., Yoneda, T., Kaneko, K., 2011c. Determination of three-dimensional
- 393 microcrack distribution and principal axes for granite using a polyhedral specimen, *Int.*
- 394 *J. Rock Mech. Min. Sci.* 48, 316-335.
- 395 Nara, Y., Morimoto, K., Yoneda, T., Hiroyoshi, N., Kaneko, K., 2011d. Effects of
- 396 humidity and temperature on subcritical crack growth in sandstone. *Int. J. Solids*
- 397 *Struct.* 48, 1130-1140.
- 398 Nara, Y., Morimoto, K., Hiroyoshi, N., Yoneda, T., Kaneko, K., Benson, P.M., 2012.
- 399 Influence of relative humidity on fracture toughness of rock: implications for
- 400 subcritical crack growth. *Int. J. Solids Struct.* 49, 2471-2481.
- 401 Nara, Y., Nakabayashi, R., Maruyama, M., Hiroyoshi, N., Yoneda, Y., Kaneko, K., 2014.
- 402 Influences of electrolyte concentration on subcritical crack growth in sandstone in
- 403 water. *Eng. Geol.* 179, 41-49
- 404 Nasser, M.H.B., Mohanty, B., Robin, P.-Y.F., 2005. Characterization of microstructures
- 405 and fracture toughness in five granitic rocks. *Int. J. Rock Mech. Min. Sci.* 42, 450-

406 460.

407 Nasser, M.H.B., Schubnel, A., Young, R.P., 2007. Coupled evolutions of fracture

408 toughness and elastic wave velocities at high crack density in thermally treated

409 Westerly granite. *Int. J. Rock Mech. Min. Sci.* 44, 601-616.

410 Nasser, M.B.H., Schubnel, A., Benson, P.M., Young, R.P., 2009. Common evolution of

411 mechanical and transport properties in thermally cracked Westerly granite at

412 elevated hydrostatic pressure. *Pure Appl. Geophys.* 166, 927-948.

413 Norton, D., Knapp, R., 1977. Transport phenomena in hydrothermal systems: the nature

414 of porosity. *Am. J. Sci.* 227, 913-936.

415 Olsen, H.W., 1966. Darcy's law in saturated kaolinite. *Water Resour. Res.* 2, 287-295

416 Oron, A.P., Berkowitz, B., 1998. Flow in rock fractures: the local cubic law assumption

417 reexamined. *Water Resour. Res.* 34, 2811-2825.

418 Pratt, H.R., Swolfs, H.S., Brace, W.F., Black, A.D., Handin, J.W., 1977. Elastic and

419 transport properties of an in situ jointed granite. *Int. J. Rock Mech. Min. Sci. &*

420 *Geomech. Abstr.* 14, 35-45.

421 Sanada, H., Hikima, R., Tanno, T., Matsui, H., Sato, T., 2013. Application of differential

422 strain curve analysis to the Toki granite for in situ stress determination at the

423 Mizunami underground research laboratory, Japan. *Int. J. Rock Mech. Min. Sci.*

424 59, 50-56.

425 Sausse, J., Jacquot, E., Fritz, B., Leroy, J., Lespinasse, M., 2001. Evolution of crack

426 permeability during fluid-rock interaction. Example of the Brézouard granite

427 (Vosges, France). *Tectonophysics* 336, 199-214.

428 Schubnel, A., Nishizawa, O., Masuda, K., Lei, X.J., Xue, Z., Gueguen, Y., 2003.

429 Velocity measurements and crack density determination during wet triaxial

430 experiments on Oshima and Toki granites. *Pure Appl. Geophys.* 160, 869-887.

- 1 Suzuki, K., Oda, M., Yamazaki, M., Kuwahara, T., 1998. Permeability change in granite  
2  
3  
4 432 with crack growth during immersion in hot water. *Int. J. Rock Mech. Min. Sci.* 35,  
5  
6 433 907-921.  
7  
8  
9 434 Unger, A. J. A., Mase, C.W., 1993. Numerical study of the hydromechanical behavior of  
10  
11 435 two rough fracture surfaces in contact. *Water Resour. Res.* 29, 2101-2114.  
12  
13 436 Vinciguerra, S., Trovato, C., Meredith, P.G., Benson, P.M., 2005. Relating seismic  
14  
15 437 velocities, thermal cracking and permeability in Mt. Etna and Iceland basalts. *Int.*  
16  
17 438 *J. Rock Mech. Min. Sci.* 42, 900-910.  
18  
19  
20 439 Walsh, J.B., 1965. The effect of cracks on the compressibility of rock. *J. Geophys. Res.*  
21  
22 440 70, 381-389.  
23  
24  
25 441 Walsh, J.B., 1981. Effect of pore pressure and confining pressure on fracture  
26  
27 442 permeability. *Int. J. Rock Mech. Min. Sci. & Geomech. Abstr.* 18, 429-435.  
28  
29  
30 443 Wang, G., Mitchell, T.M., Meredith, P.G., Nara, Y., Wu, Z., 2016. Influence of gouge  
31  
32 444 thickness on permeability of macro-fractured basalt. *J. Geophys. Res.* 121, 8472-8487.  
33  
34  
35 445 Witherspoon, P.A., Wang, J.S.Y., Iwai, K., Gale, J.E., 1980. Validity of cubic law for fluid  
36  
37 446 flow in a deformable rock failure. *Water Resour. Res.* 16, 1016-1024.  
38  
39  
40 447 Yamamoto, K., Yoshida, H., Akagawa, F., Nishimoto, S., Metcalfe, R., 2013. Redox front  
41  
42 448 penetration in the fractured Toki granite, central Japan: An analogue for redox  
43  
44 449 reactions and redox buffering in fractured crystalline host rocks for repositories of  
45  
46 450 long-lived radioactive waste. *Appl. Geochem.* 35, 75-87.  
47  
48  
49 451 Yamasaki, S., Zwingmann, H., Yamada, K., Tagami, T., Umeda, K., 2013. Constraining the  
50  
51 452 timing of brittle deformation and faulting in the Toki granite, central Japan. *Chem.*  
52  
53 453 *Geol.* 351, 168-174.  
54  
55  
56 454 Yuguchi, T., Tagami, M., Tsuruta, T., Nishiyama, T., 2012. Three-dimensional fracture  
57  
58 455 distribution in relation to local cooling in a granitic body: An example from the Toki  
59  
60  
61  
62  
63  
64  
65

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

456 granitic pluton, Central Japan. Eng. Geol. 149-150, 35-46.

457 Zhang, M., Takahashi, M., Morin, R.H., Esaki, T., 2000. Evaluation and application of the

458 transient-pulse technique for determining the hydraulic properties of low-permeability

459 rocks – Part 1: theoretical evaluation. Geotech. Test. J. 23, 83-90.

460 Zhang, M., Takahashi, M., Morin, R.H., Esaki, T., 2000. Evaluation and application of the

461 transient-pulse technique for determining the hydraulic properties of low-permeability

462 rocks – Part 2: experimental application. Geotech. Test. J. 23, 91-99.

Table

Table 1 Summary of the hydraulic conductivity for Toki granite at elevated pressures

|                                                              | Effective confining pressure<br>[MPa] | Hydraulic conductivity<br>[m/s]                 |
|--------------------------------------------------------------|---------------------------------------|-------------------------------------------------|
| Intact specimen<br>(TG-i)                                    | 1.07                                  | $3.75 \times 10^{-12} \pm 1.79 \times 10^{-14}$ |
|                                                              | 1.98                                  | $4.66 \times 10^{-12} \pm 6.89 \times 10^{-14}$ |
|                                                              | 3.05                                  | $3.98 \times 10^{-12} \pm 6.90 \times 10^{-14}$ |
|                                                              | 4.04                                  | $2.97 \times 10^{-12} \pm 1.64 \times 10^{-14}$ |
|                                                              | 5.04                                  | $2.78 \times 10^{-12} \pm 2.38 \times 10^{-14}$ |
|                                                              | 5.96                                  | $2.62 \times 10^{-12} \pm 2.72 \times 10^{-14}$ |
|                                                              | 7.00                                  | $2.27 \times 10^{-12} \pm 4.72 \times 10^{-14}$ |
|                                                              | 8.02                                  | $3.34 \times 10^{-12} \pm 3.27 \times 10^{-14}$ |
|                                                              | 9.01                                  | $4.62 \times 10^{-12} \pm 3.39 \times 10^{-14}$ |
| Macro-fractured specimen<br>without filling<br>(TG-f)        | 0.95                                  | $5.56 \times 10^{-8} \pm 2.54 \times 10^{-9}$   |
|                                                              | 2.97                                  | $1.71 \times 10^{-8} \pm 5.28 \times 10^{-10}$  |
|                                                              | 3.78                                  | $1.03 \times 10^{-8} \pm 4.25 \times 10^{-10}$  |
|                                                              | 4.94                                  | $7.09 \times 10^{-9} \pm 2.35 \times 10^{-10}$  |
|                                                              | 6.87                                  | $2.87 \times 10^{-9} \pm 9.90 \times 10^{-10}$  |
|                                                              | 8.94                                  | $3.62 \times 10^{-9} \pm 9.20 \times 10^{-10}$  |
| Specimen with a mineral vein<br>(TG-v)                       | 1.22                                  | $8.63 \times 10^{-12} \pm 1.56 \times 10^{-13}$ |
|                                                              | 1.97                                  | $6.42 \times 10^{-12} \pm 7.34 \times 10^{-14}$ |
|                                                              | 2.83                                  | $5.65 \times 10^{-12} \pm 1.06 \times 10^{-13}$ |
|                                                              | 3.84                                  | $6.70 \times 10^{-12} \pm 3.65 \times 10^{-14}$ |
|                                                              | 4.84                                  | $5.90 \times 10^{-12} \pm 9.86 \times 10^{-14}$ |
|                                                              | 6.69                                  | $4.76 \times 10^{-12} \pm 6.52 \times 10^{-14}$ |
|                                                              | 8.89                                  | $4.33 \times 10^{-12} \pm 4.48 \times 10^{-14}$ |
| Specimen with a macro-fracture<br>filled with clay<br>(TG-c) | 0.97                                  | $7.59 \times 10^{-11} \pm 2.13 \times 10^{-12}$ |
|                                                              | 2.02                                  | $4.43 \times 10^{-11} \pm 1.01 \times 10^{-12}$ |
|                                                              | 3.03                                  | $3.21 \times 10^{-11} \pm 4.96 \times 10^{-13}$ |
|                                                              | 4.08                                  | $1.98 \times 10^{-11} \pm 3.70 \times 10^{-13}$ |
|                                                              | 5.03                                  | $1.67 \times 10^{-11} \pm 1.64 \times 10^{-13}$ |
|                                                              | 7.01                                  | $1.25 \times 10^{-11} \pm 5.16 \times 10^{-14}$ |
|                                                              | 9.03                                  | $1.06 \times 10^{-11} \pm 4.94 \times 10^{-14}$ |

**Figure caption**

Fig. 1 Photos of Toki granite. (a): Rock core sample (65-mm diameter) with a macro-fracture, (b): Rock core sample (50-mm diameter) with a mineral vein, (c): Rock core sample (65-mm diameter) with clay filling.

Fig. 2 Photos of (a) the intact specimen (TG-i), (b) macro-fractured specimen (TG-f), (c) specimen with a vein of fine-grained minerals (TG-v), and (d) specimen with a macro-fracture filled with clay (TG-c). Diameter and length of the specimens are 50 and 25 mm, respectively.

Fig. 3 Photomicrographs of (a) the intact specimen (TG-i), (b) specimen with a vein of fine-grained minerals (TG-v), and (c) specimen with a macro-fracture filled with clay (TG-c). Length and height of the photomicrographs are 1.95 and 1.25 mm, respectively.

Fig. 4 Schematic of the permeability measurement system.

Fig. 5 Temporal changes of the upstream and downstream hydraulic pressure difference for (a) the intact specimen (TG-i), (b) specimen with a vein of fine-grained minerals (TG-v), and (c) specimen with a macro-fracture filled with clay (TG-c) at a confining pressure of 2 MPa obtained by the transient pulse method. The accuracy of the upstream and downstream hydraulic pressure difference was 0.35 kPa.

Fig. 6 Temporal change of the upstream and downstream hydraulic pressure difference in the macro-fractured specimen (TG-f) at a confining pressure of 2 MPa obtained by the constant flow method. The accuracy of the upstream and downstream hydraulic pressure difference was 0.35 kPa.

Fig. 7 Relationships between permeability and effective confining pressure for an intact sample, a macro-fractured sample, a sample containing a mineral vein, and a

1  
2  
3  
4  
5  
6  
7  
8  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65

492 sample containing a macro-fracture filled with clays of Toki granite.

493 Fig. 8 Relationships between hydraulic aperture of equivalent fracture and effective  
494 confining pressure for Toki granite.

495

496

497 The English in this document has been checked by native speakers of English, from an  
498 English editing service company:

499 <https://www.zenis.co.jp/eng/index.html>

500

501



Figure1b

[Click here to download Figure Figure\\_1b\(core\\_vein\).jpg](#)



Figure1c

[Click here to download Figure Figure\\_1c\(core\\_clay\).jpg](#)











Figure3a



















