

On approximation algorithms for intersection graphs of rectangles

矩形によるインターセクショングラフに関する近似アルゴリズムについて

山崎 浩一

Koichi YAMAZAKI

群馬大学工学部情報工学科

〒 376-8515 群馬県桐生市天神町 1-5-1

koichi@comp.gunma-u.ac.jp

Abstract: In this paper we show some graph theoretical properties of intersection graphs on rectangles and that the minimum coloring problem can be approximated within ratio $O((\log |V(G)|)^2)$ for the intersection graphs represented by sets of rectangles on the plane.

Keywords: Intersection graphs, rectangles, approximation algorithms, maximum weight independent set problem, minimum coloring problem;

1 Definitions and notation

Let $G = (V, E)$ be a graph. We denote the subgraph of G induced by $V' \subseteq V$ by $G[V']$, the degree of vertex u in G by $d_G(u)$, the maximum degree of vertex in G by Δ_G , the neighborhoods of v by $N_G(v)$, and $\{v\} \cup N_G(v)$ by $N_G^+(v)$. If G is understood, then we often omit the inscription G in $d_G(u)$, Δ_G , $N_G(v)$, and $N_G^+(v)$.

Let $\mathcal{F} = \{S_1, \dots, S_k\}$ be a family of nonempty subset of a set S . We will call the pair $(\mathcal{F}, S)$ *representation*. We will refer to the set S as the *host* and the subsets S_i as *objects*. A graph G is an *intersection graph represented by a representation* $(\mathcal{F}, S)$ if $G = (\mathcal{F}, E)$ such that $\forall S_i, S_j \in \mathcal{F}$ ($i \neq j$), $\{S_i, S_j\} \in E$ iff $S_i \cap S_j \neq \emptyset$. Let $\mathcal{R} = (\mathcal{F} = \{S_1, \dots, S_k\}, S)$ be a representation. We will say that $\mathcal{R}$ is *unit* if the objects of $\mathcal{F}$ have the same shape. $\mathcal{R}$ is *injective* if $S_i = S_j$ implies $i = j$ (i.e. the subsets are distinct). Objects we consider in the paper are open.

A *closed (open) rectangle* on the plane is a set R_i of points such that $\exists (x_1, y_1), (x_2, y_2)$ ($x_1 \leq x_2, y_1 \leq y_2$) for which $R_i = \{(x, y) \mid x_1 \leq x \leq$

$x_2, y_1 \leq y \leq y_2\}$ ($\{(x, y) \mid x_1 < x < x_2, y_1 < y < y_2\}$ respectively). We denote the projection of a rectangle R_i on the x-axis (y-axis) $I_x(R_i)$ ($I_y(R_i)$ respectively). Let R be a sets of rectangles on the plane. R is *x-axis (y-axis) non-proper* if $\forall R_i, R_j \in R$ $I_x(R_i) \subsetneq I_x(R_j)$ and $I_x(R_j) \subsetneq I_x(R_i)$ ($I_y(R_i) \subsetneq I_y(R_j)$ and $I_y(R_j) \subsetneq I_y(R_i)$) respectively). R is *strongly non-proper* if R is x and y-axis non-proper.

Let I be a sets of intervals on the real line. A graph G is an *interval graph represented by I* if G is an intersection graph represented by I (so the host is the real line in this case). Let $MI = \{A_1, \dots, A_k\}$ be a set such that A_i ($\forall 1 \leq i \leq k$) is a union of intervals on the real line. A graph G is a *multiple interval graph represented by MI* if G is an intersection graph represented by MI (so the host is the real line in this case).

2 Known techniques

In the section, we will review several techniques (and properties) which are useful in designing ap-

proximation algorithms for the problems.

2.1 Claw-free property

A graph is k *claw-free* if the graph does not have $K_{1,k}$ as induced subgraph (See [18]). A set of graphs is *claw-free* if there is a positive integer k such that all graphs in the set are k claw-free. For example, the following types of intersection graphs have claw-free property.

Unit intersection graphs

Most of intersection graphs with unit representations have the claw-free property. For example, a graph represented by unit iso-oriented rectangles on the plane is a 5 claw-free graph. A graph represented by unit disks on the plane is a 7 claw-free graph (in our definition all objects we consider are open) (See [15]).

Representations with objects of bounded area

Let G be a graph represented by a set objects $\mathcal{F}$ on the plane with following two properties; there is a positive integer k such that the area of each object in $\mathcal{F}$ is at most k , and any two intersecting objects in $\mathcal{F}$ share a region with an area of at least one. Then it is easy to see that all graph represented by $\mathcal{F}$ on the plane are $k + 1$ claw-free graphs.

The claw-free property plays an important role in the two (or more) dimensional packing problem (See [2, 15]), because packing problem can be thought as a maximum independent set problem, and it is known that the independent number of a 3 claw-free weighted graph can be computed in polynomial time [16] and also that the independent number of a k claw-free graph can be approximated within ratio of $(k + 1)/2$ for unweighted graphs [10] and k for weighted graphs [11].

2.2 The most left object strategy

Let G be an intersection graph of strongly non-proper rectangles on the plane, and let $v \in V(G)$

be the vertex corresponding to the most left object in a representation of G . Then since $G[N_G^+(v)]$ is a 3 claw-free graph, we have $\alpha(G[N_G^+(v)]) \leq 2$. Similarly, for an intersection graph G of unit disks on the plane, we have $\alpha(G[N_G^+(v)]) \leq 3$ (note that in our definition all objects we consider are open) [15]. Clearly if G is an intersection graph of strongly non-proper rectangles (and/or unit disk) on the plane then so is an induced subgraph of G . Hence the intersection graphs of strongly non-proper rectangles on the plane (and/or of unit disks on the plane [15]) have the following properties: Let $\mathcal{I}$ be a set of intersection graphs.

- $\exists$ a small integer k such that $\forall G \in \mathcal{I}, \exists v \in V(G)$ for which $\alpha(G[N_G^+(v)]) \leq k$,
- $\forall G \in \mathcal{I}$ and $\forall V' \subseteq V(G), G[V'] \in \mathcal{I}$.

Using this properties, Marathe et al. showed better approximation algorithms for minimum coloring problem and maximum independent set problem for unit disk graphs [15]. The method in [15] leads the the following proposition (See concluding remarks in [15]). The proofs (for minimum coloring problem) is quite similar to the unit disk case presented in [15], hence are omitted.

Proposition 2.1 *Let $\mathcal{I}$ be a set of graphs with properties that (1) $\exists$ a small integer k such that $\forall G \in \mathcal{I}, \exists v \in V(G)$ for which $\alpha(G[N_G^+(v)]) \leq k$, and (2) $\forall G \in \mathcal{I}$ and $\forall V' \subseteq V(G), G[V'] \in \mathcal{I}$. Then, minimum coloring problem and (unweighted) maximum independent set problem for $\mathcal{I}$ can be approximated within ratio of k .*

Corollary 2.2 *Let R be a strongly non-proper set of rectangles on the plane. Then minimum coloring problem and (unweighted) maximum independent set problem for intersection graphs represented by R can be approximated within ratio of 2.*

2.3 Shifting strategy

Hochbaum and Maass introduced a method, called *shifting strategy*, which applies to covering and packing problems in the plane in order

to yield a polynomial time approximation scheme [8, 9].

2.4 Decomposition strategy

In [14], S.Khanna et al. introduced the following simple and useful technique to partition a graph G represented by rectangles on the plane into $O((\log |V(G)|)^2)$ 9 claw-free induced subgraphs of G : Partition the set of given rectangles into $\lceil \log |V(G)| \rceil^2$ classes (i, j) , $1 \leq i \leq \lceil \log |V(G)| \rceil$ and $1 \leq j \leq \lceil \log |V(G)| \rceil$. The class (i, j) comprises all rectangles with width $\in [2^{i-1} + 1, 2^i]$, and height $\in [2^{j-1} + 1, 2^j]$. Then it is easy to see that each intersection graph represented by rectangles in class (i, j) (on the plane) is a 9 claw-free graph. We will refer to the technique as *decomposition strategy*.

Decomposition strategy is very simple but useful. For example, we can give much more simple proof than one in chapter 6 in [4] for the following theorem by using decomposition strategy.

Theorem 2.3 $\tau(n) \geq n/\lceil \log_2 n \rceil$ for all $n \geq 3$, where $\tau(n) = \max\{k \mid \text{every interval graph of size } n \text{ has a 3 claw-free induced subgraph of size } k\}$.

3 Results

3.1 Graph theoretical properties of rectangle graphs

Forbidden induced subgraphs

Lemma 3.1 Let R be a set of rectangles on the plane. And let G be the intersection graph represented by R . Then, G does not have an octahedron as an induced subgraph.

Chromatic number and clique number

Let R be a set of rectangles on the plane. And let G be the intersection graph represented by R . In [1], Asplund and Grünbaum showed that $4\omega(G)^2 > \chi(G)$. If R is strongly non-proper, then we have $4\omega(G) + 1 \geq \chi(G)$, because $\omega(G) \geq$

$\lceil \Delta(G)/4 \rceil$ and $\Delta(G) + 1 \geq \chi(G)$. By using the most left object strategy, we can show the following slightly better upper bound.

Proposition 3.2 Let G be an intersection graph represented by a strongly non-proper set of rectangles on the plane. Then the chromatic number of G is at most two times the clique number of G plus one.

Proof. Let $\mathcal{G}$ be the set of intersection graphs represented by a strongly non-proper set of rectangles on the plane. Any $G \in \mathcal{G}$ has a vertex v such that $d_G(v)$ is at most 2ω . For any induced subgraph G' of G , G' is also in $\mathcal{G}$, and $\omega(G') \leq \omega(G)$. Thus, $\chi(G) \leq 2\omega(G) + 1$. $\square$

3.2 An approximation algorithm for minimum coloring problem

Theorem 3.3 The minimum coloring problem can be approximated within ratio $O((\log |V(G)|)^2)$ for the intersection graphs represented by sets of rectangles on the plane.

Proof. By using decomposition strategy, we have at most $O((\log |V(G)|)^2)$ 9 claw-free subgraphs G_{ij} of G ($1 \leq i, j \leq \log |V(G)|$). Obviously for each subgraph G_{ij} , $\chi(G_{ij}) \leq \chi(G)$. From proposition 2.2, the problem for each subgraph G_{ij} can be approximated within ratio 7. This means that $\sum_{ij} (7 \times \chi(G_{ij})) \leq \sum_{ij} (7 \times \chi(G))$ is $O((\log |V(G)|)^2) \times \chi(G)$, thus the proof is complete. $\square$

4 Summary

Maximum independent set problem

object	unweighted	weighted
unit disk	PTAS [12], 3 [15]	—
unit rectangle	PTAS [8, 9], 2^{*1}	—
SNP rectangles	2^{*1}	3.25 [2]
rectangles	—	$O(\log n)$ [14]

Minimum coloring problem

object	injective	no restriction
unit disk	——	3 [15]
unit rectangle	——	2^{*1}
SNP rectangles	——	2^{*1}
rectangles	——	$O((\log n)^2)^{*2}$

*1: From corollary 2.2.

*2: From proposition 2.1 and decomposition strategy.

5 Acknowledgment

The research is partly supported by the Grant-in-Aid for Scientific Research on Priority Areas of Ministry of Education, Science, Sports and Culture of Japan under Grant No. 10205202. and the Scientific Grant-in-Aid for Encouragement of Young Scientists of Ministry of Education, Science, Sports and Culture of Japan.

参考文献

- [1] E.Asplund and B.Grünbaum, On a coloring problem, *Math. Scand.* 8 (1960) 181-188.
- [2] V.Bafna, B.Narayanan, and R.Ravi, Nonoverlapping local alignments (Weighted independent sets of axis parallel rectangles), *Discrete Applied Math.* 71 (1996) 41-53.
- [3] B.N.Clark, C.J.Colbourn, and D.S.Johnson, Unit disk graphs, *Discrete Math.* 86 (1990) 165-177.
- [4] P.C.Fishburn, Interval orders and interval graphs - A Study of Partially Ordered Sets -, A Wiley-Interscience Publication, 1985.
- [5] M.C.Golumbic, Interval graphs and related topics, *Discrete Math.* 55 (1985) 113-121.
- [6] A.Gyárfás, On the chromatic number of multiple interval graphs and overlap graphs, *Discrete Math.* 55 (1985) 161-166.
- [7] D.S.Hochbaum, Efficient bounds for the stable set, vertex cover and set packing problems, *Discrete Appl. Math.* 6 (1983) 243-254.
- [8] D.S.Hochbaum and W.Maass, Approximation schemes for covering and packing problems in image processing and VLSI, *JACM* 32 (1985) 130-136.
- [9] D.S.Hochbaum, Various notions of approximations: good, better, best, and more, in: D.S.Hochbaum, ed., *Approximation Algorithms for NP-HARD PROBLEMS* (PWS Publishing Company, 1997) 339-446.
- [10] M.M.Halldórson, Approximating discrete collections via local improvements, *Proceedings of the Sixth Annual ACM-SIAM Symposium on Discrete Algorithms*, (1995) 160-169.
- [11] D.S.Hochbaum, Efficient bounds for the stable set, vertex cover and set packing problems, *Discrete Applied Math.*, 6 (1983) 243-254.
- [12] H. B. Hunt, M. V. Marathe, V. Radhakrishnan, and S. S. Ravi, A unified approach to approximation schemes for NP- and PSPACE-hard problems for geometric graphs, *Algorithms—ESA '94, Second Annual European Symposium, LNCS 855* (1994) 424-435.
- [13] H.Imai and T.Asano, Finding the connected components and a maximum clique of an intersection graphs of rectangles in the plane, *J. Algorithms*, 4 (1983) 310-323.
- [14] S.Khanna, S.Muthukrishnan and M.Paterson, On approximating rectangle tiling and packing, *Proceedings of the Ninth Annual ACM-SIAM Symposium on Discrete Algorithms*, (1998) 384-393.
- [15] M.V.Marathe, H.Breu, H.B.Hunt III, S.S.Ravi, and D.J.Rosenkrantz, Simple heuristics for unit disk graphs, *Networks* 25 (1995) 59-68.

- [16] G.J.Minty, On maximal independent sets of vertices in claw-free graphs, *J. Combin. Theory Ser. B* 28 (1980) 284-304.
- [17] D.T.Lee, and J.Y-T.Leung, On the 2-dimensional channel assignment problem, *IEEE Trans. Compute.*, c-33 (1984) 2-6.
- [18] R.Faudaree, E.Flandrin, and Z.Ryjáček, Claw-free graphs — A survey, *Discrete Math.* 164 (1997) 87-147.