

は、時間と共に低周波側に移動し、平均エネルギーの増大が確認できた。ピークの $2\omega_e$ からのずれは、高速電子群が 50 keV の Maxwell 分布であるとすれば説明できる。これは硬 X 線波高分析の結果とも矛盾しない。また輻射強度は、高周波印加と同時に急激に増大し、約 10 msec で飽和する。これは、エネルギーと密度が急激に増大することを示している。

16. THERMAL INSULATION

— Minimization of Heat Leak Into a Cryogenic Storage Space —

Borauzima M. S. RUGAIGANISA

The final aim of the entire research is to find the most technically effective and economic way to store large quantities of liquid helium with minimal losses due to evaporation. Before design and construction of the final storages pertinent heat transfer data had to be obtained. To do this a 220-liter SUS 304 test dewar was constructed.

The helium container of the dewar hangs by the neck around which there is a 25-litre liquid nitrogen tank. Surrounding the container is a copper radiation shield which is shielded from the outer jacket radiation by 30 layers of Al-Polyester-Al superinsulation foils. Additionally, the shield is cooled by a "cryominirefrigerator" to 45 K. Around the refrigerator head is wound a manganin-wire heater used to raise the shield temperature as required. The dewar has 59 temperature measurement points.

During this run no superinsulations were wrapped around the container. The main objectives were to determine the effective emissivity, ϵ between the container and shield surface; and, the efficiency, E of the evaporated helium gas in stopping the conduction heat leak, C from reaching the container from the liquid nitrogen temperature of 77.3 K.

To do this, two main experiments, based on the liquid evaporation loss method, were conducted. In the first, a metal-oxide resistor heater was directly introduced into the liquid. The heating power was varied to different values and the corresponding steady-state evaporation flow rate, f was measured. In the second experiment, the radiation shield temperature was varied and again f was measured.

From the results of Experiment 2 the value $\epsilon = 0.027$ was estimated. It was confirmed when, by using it, results from both experiments agreed. The conduction stoppage efficiency was sub-

sequently obtained as $E_0 = 80\%$.

Still, it was observed that under these circumstances the ratio of the conduction leak, C reaching the container to the minimum radiation, R from the shield was $C/R = 5$. This is large and could be cut to less than 3 by replacing a part of the SUS 304 neck tube with CFRP. Preparations for this have been accomplished and this modification will be performed before any further experimental work resumes.

○ 大阪大学基礎工学研究科物理系専攻

- | | |
|---|---------|
| 1. アルカリ原子吸着系の統計力学 | 垣谷 公德 |
| 2. 超伝導近接効果における磁性不純物の影響及び $\text{REBa}_2\text{Cu}_3\text{O}_{7-\delta}$ 超伝導体の研究 | 兼子 哲幸 |
| 3. 固体 LiH の金属化圧の計算と状態方程式 | 川上 展弘 |
| 4. Y系酸化物高温超伝導体の ^{57}Fe Mössbauer 効果 | 北川 英夫 |
| 5. 高温超伝導体の熱的・磁氣的性質 | 小林 達生 |
| 6. $\text{YBa}_2(\text{Cu}_{1-x}\text{Fe}_x)_3\text{O}_y$ の帯磁率及び CoTi の超伝導 | 坂上 栄人 |
| 7. ゲルマニウムカルコゲナイドの高圧下における相転移 | 阪本 一朗 |
| 8. 干渉性放射光によるモノシランのK殻励起光解離 | 繁政 英治 |
| 9. Fe-Pd 合金の $\text{bcc}(\text{bct})$ マルテンサイトの変態機構に関する研究 | 田中 克志 |
| 10. グラファイト層間化合物 ($\text{MCl}_2\text{-GIC}$) の秩序化の動的側面
ースピングラスとの類似性について | 田中 信幸 |
| 11. Mn_3MC ($\text{M} = \text{Zn}, \text{Ga}, \text{In}, \text{Sn}$) の電子状態と磁性 | 永井 秀康 |
| 12. 高圧下における KDP 及び DKDP の単結晶X線構造解析 | 知野 豊治 |
| 13. ダイヤモンドの NV 中心の永続的ボールバーニング効果の研究 | 出水 祐三 |
| 14. 高速パルス磁場下の磁化過程 | 中川 匡夫 |
| 15. X線回折法による $(\text{NH}_4)_2\text{BeF}_4$ 不整合相に対する電場効果の研究 | 長田 誠 |
| 16. ダイヤモンド焼結体アンビルによる超高压下での高温発生 | 仁田脇 莊一郎 |
| 17. 金属表面での遮蔽効果 | 橋村 淳司 |
| 18. X線回折による固体ハロゲンの圧力誘起相転移の研究 | 長谷喜代司 |